

GOLD

7210

PREMIUM  
**RUST-OLEUM®**  
**HAMMERED**

UNIQUE HAMMERED FINISH

BEFORE  
& AFTERSTOPS  
RUST®

**WARNING!**  
**FLAMMABLE**  
**LIQUID AND VAPOR**

See Other Cautions  
on Back Panel.

32 FL. OZ. (1 QT.)

Hides Surface Imperfections • No Primer Needed

**¡ADVERTENCIA!**  
**LÍQUIDO Y VAPOR**  
**INFLAMABLES**

Ver al dorso  
precauciones adicionales.

.946 L

**Rust-Oleum® Hammered Metal Finish provides a long-lasting protective barrier that seals out moisture and protects the underlying surface from rust and corrosion. The unique hammered finish covers imperfect surfaces eliminating the need to sand to bare metal. Ideal for scratched, weathered, and sound rusted metal. The hammered finish decorates and protects metal, wood, concrete, stone and more.**

**Directions:** Use outdoors or in a well-ventilated area, when temperature is above 60°F (15°C) and humidity is below 85% to ensure proper drying. Do not apply to surfaces that will exceed 200°F (93°C). Remove loose rust and loose paint with a wire brush or sandpaper. It is not necessary to remove tightly adhering rust or old paint. Clean surface with soap and water, rinse and let dry. Lightly sand glossy surfaces and wipe away residual dust with a clean cloth. Clean with soap and water, rinse and let dry. Do not apply a primer. Stir thoroughly before and during use. Apply by brush or roller. A short nap roller is recommended for large, flat surfaces. Avoid painting in direct sunlight or on hot surfaces. Avoid excessive brushing as this will reduce film thickness and protection.

Apply 2 coats for full coverage, best appearance, and maximum rust protection. Make sure that corners, edges and heavily pitted areas are adequately covered. Apply second coat after the first coat is dry to the touch (usually in 30 minutes). Second coat must be applied within 4 hours or after 7 days. Dries to handle in 60-90 minutes at 77°F (25°C) and 50% relative humidity.

Thinning is normally not required for brush or roller application. Clean brush, roller, and other tools with a xylol thinner immediately after use.

**Contains: Xylene and Petroleum Distillates.** VAPOR HARMFUL MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. CAUSES EYE, SKIN, NOSE AND THROAT IRRITATION. NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Do not breathe vapors, spray mist, sanding dust or overspray. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Keep away from heat, sparks, and flame. VAPORS MAY CAUSE FLASH FIRE. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. **Use only with adequate ventilation.** Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Close container after each use. **First Aid:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. **WARNING:** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm. **KEEP OUT OF REACH OF CHILDREN. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.** Unleaded—Safe for use on children's toys, furniture, etc. **Max. VOC 450 g/l**

**We stand behind our products. If you are dissatisfied with this product, contact our Customer Service Department for a refund of the product purchase price.**

An RPM Company

www.rustoleum.com

©2000 Rust-Oleum Corporation

Made in USA

RLO5109 0300

**Contiene: Xileno y Destilados de petróleo.** LAS EMANACIONES SON DAÑINAS. PUEDEN AFECTAR AL CEREBRO O AL SISTEMA NERVIOSO CAUSANDO MAREOS, JAQUECAS O NAUSEA. IRRITA LOS OJOS, LA PIEL, LA NARIZ Y LA GARGANTA. AVISO: En algunos estudios se ha observado que la sobreexposición ocupacional repetida y prolongada a los solventes causa daño permanente al cerebro y al sistema nervioso. No respire las emanaciones, la nube del rocío, el polvo del lijado, ni el rocío. Asegúrese de que entre y circule el aire fresco durante la aplicación y el secado. Si experimenta lacrimación en los ojos, jaquecas o mareos, o si un muestreo del aire indica niveles de emanación/rocío superiores a los límites correspondientes, póngase protección respiratoria adecuada (con certificación NIOSH/MSHA) durante y después de la aplicación. Por favor siga instrucciones del fabricante para uso apropiado del respiratorio. Evite el contacto con los ojos, piel y ropa. Lávese cuidadosamente después de cada aplicación. Mantener lejos de fuentes de calor, chispas y llamas vivas. EL VAPOR PUEDE CAUSAR LLAMARADAS. No fume. Apague cualquier llama y llamas pilotas, apague la estufa, los calentadores, los motores eléctricos y cualquier otra fuente de ignición durante el uso y hasta cuando todos los vapores se hayan desperdiciado. **Aplique el producto solamente con ventilación adecuada.** Evite la acumulación de emanaciones abriendo todas las ventanas y puertas para lograr ventilación en todas las direcciones. Vuelva a colocar la tapa después de cada uso. **PRIMEROS AUXILIOS:** Si sufre dificultad para respirar, abandone el área y respire aire fresco. Si la dificultad para respirar persiste, busque asistencia médica inmediatamente. En caso de contacto con los ojos, enjuáguelos de inmediato con suficiente agua durante un mínimo de 15 minutos y busque atención médica; en caso de contacto con la piel, lave completamente el área afectada con agua y jabón. Si se ingiere el producto, busque atención médica prontamente. Si el producto se derrama, encierre el material derramado y recójalo con absorbente inerte. Elimine el absorbente contaminado, el recipiente y la cantidad no utilizada de acuerdo con las leyes locales, estatales y federales. **ADVERTENCIA:** Este producto contiene químicos que son conocidos en el Estado de California por causar cáncer y defectos de nacimiento u otros daños al sistema reproductivo. MANTÉNGALO FUERA DEL ALCANCE DE LOS NIÑOS. EL USO INAPROPIADO INTENCIONAL CONCENTRANDO E INHALANDO EL CONTENIDO PUEDE SER DAÑINO O MORTAL. No contiene plomo — Puede utilizarse para los juguetes de los niños, muebles, etc.