LEAKSEAL®
FLEXIBLE RUBBER COATING

RUST-OLEUM®
HIGH PERFORMANCE

Creates a water-tight seal

LeakSeal® Flexible Rubber Coating Seals leaks and fills cracks and holes. This easy-to-use formula sprays on semi-smooth and creates a rubberized, water-tight seal that keeps out water and prevents rust and corrosion.

FEATURES & BENEFITS

✔ Dries to a flexible and paintable finish – won't sag or drip

✔ Water-tight seal prevents moisture penetration and corrosion

✔ Ideal for gutters, roofs, flashings, duct work, PVC, etc.

✔ Utility colors are perfect for touch-up and repair electric utility structures

✔ Can be top-coated with latex or alkyd based paints

"We use LeakSeal at the substations along the coast where many of the bolt holes, welds, edges and corners of the circuit breaks are rusting. LeakSeal is easy to apply and seals cracks quickly with no mess."

– Thomas,
Utility Transmission Supervisor

RUST-OLEUM
INDUSTRIAL BRANDS

LEAKSEAL® FLEXIBLE RUBBER COATING

QUICK FACTS

FILL WEIGHT	15 oz. (Clear 13.75 oz.)
PRACTICAL COVERAGE	8.0 sq. ft./can
TACK-FREE DRY TIME	20-30 minutes
HANDLE DRY TIME	45-60 minutes
RECOAT DRY TIME	20-30 minutes
TOP COAT DRY TIME	24 hours
MIR	1.20 Max
ADHERES TO	Metal, Aluminum, Glavanized Metal, PVC, Concrete, Asphalt Roofing Materials, Vinyl Siding, Fiberglass and more.

Please see technical data and material safety data sheets for complete details.

COLORS

Black
266784

Clear
267453

ANSI Gray
279415

Munsell Green
279416

PRODUCT APPLICATION

Typical Applications: gutters, roofs, flashings, duct work, PVC, masonry and more.

Application:

Aerosol

Substrates:

Metal   Concrete   Plastic

MORE INFORMATION

▶ LeakSeal Aerosol Video

LeakSeal Aerosol Technical Data Sheet

⚠ LeakSeal Aerosol Material Safety Data Sheet

RUST-OLEUM
INDUSTRIAL BRANDS

Contact your Rust-Oleum representative for more information.

Phone: 800.553.8444 | Fax: 800.782.3369 | Email: customerservice@rustoleum.com

www.rustoleum.com/industrial