

TERRA COTTA SPRAY PAINT

DESCRIPTION	An indoor/outdoor decorative finish with a fine terra cotta texture. For use on a variety of surfaces including wicker, wood and metal.
APPEARANCE	Textured Matte Finish
RECOMMENDED PRIMER	7980 White Primer
PACKAGING	12 oz. can (340 g)
SURFACE PREPARATION	<p>Remove all dirt, grease, oil, salt or other contaminants by washing the surface with detergent or other suitable cleaner. Rinse thoroughly with fresh water and allow to fully dry.</p> <p>Scrape and wire brush or power tool clean to remove loose rust, scale, and deteriorated coatings. Scarify previously painted coatings or smooth surfaces to promote adhesion. Test for compatibility with existing coating.</p>
APPLICATION	<p>Apply only when air and surface temperatures are between 50°-100°F (10°-38°C) and surface is at least 5°F (3°C) above the dew point. Apply two or more light coats a few minutes apart.</p> <p>Use in properly ventilated area. Spraying can produce a fog that will travel. Protect surrounding area, clothing and skin from overspray.</p> <p>Not to be used on galvanized metal. Do not use near open flame.</p>
CLEANUP	When finished spraying, clear spray valve by turning can upside down and pushing spray button for 5 seconds. If valve clogs, twist and pull off spray tip and rinse it in a solvent such as mineral spirits. Do not stick a pin or other object into the stem. Throw away empty can in trash pickup. Do not burn or place in home trash compactor.

PHYSICAL PROPERTIES (Calculated values are shown and may vary slightly from the actual manufactured material)

RESIN TYPE	Modified Alkyd
SOLVENTS	Xylene, Acetone
VOLATILE ORGANIC COMPOUNDS	<65% by wt.
PRACTICAL COVERAGE	Approximately 12-15 sq. ft./can
DRY TIMES @ 70°F (21°C) And 50% RH	Tack Free 15 minutes Handle 1-2 hours Recoat Within 1 hour or after 48 hours
DRY HEAT RESISTANCE	200°F (94° C)
SHELF LIFE	5 Years

SAFETY (For additional information, see MSDS)

FLASH POINT LEAD-FREE	-156° F (-144° C)
--------------------------	-------------------