AQUA
WATER-BASED AEROSOL

DESCRIPTION AND USES

Rust-Oleum® Aqua Water-based Paint is a multi-purpose water-based aerosol designed to provide long lasting protection and durability both indoors and outdoors. This product is fast dry, has excellent coverage, chip resistance and color retention. It is suitable for use on metal, wicker, Styrofoam® and many other project surfaces.

PRODUCTS

SKU (12 oz. sprays)	Description
223624	Glacier White
223625	Black Ice
223635	Sand Dune
223637	Gray Primer

PRODUCT APPLICATION

PAINTING CONDITIONS

Apply only when air and surface temperatures are above 60-90ºF (16-32ºC) and humidity is below 85% to ensure proper drying.

SURFACE PREPARATION

Remove all dirt, grease, oil, salt and chemical contaminants by washing the surface with soap and water, or other suitable cleaning method. Rinse with fresh water and allow to thoroughly dry. Remove loose paint and rust with a wire brush or sandpaper. Lightly sand glossy surfaces. WARNING: If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.eps.gov/lead.

PRIMING

Use of Aqua 223637 Gray Primer promotes adhesion and enhances hiding and is especially recommended for bare wood and metal. The topcoat finish can be applied within 1 hour or after 48 hours.

PRODUCT APPLICATION (cont.)

APPLICATION

Shake can vigorously for one minute after the mixing ball begins to rattle. If mixing ball fails to rattle DO NOT STRIKE CAN. Contact Rust-Oleum. Shake often during use. Hold can upright 8-10" from surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can in motion while spraying. Apply two or more light coats a few minutes apart to avoid drips and runs. **Do not use near open flame.**

DRY & RECOAT TIMES

Dry and recoat times are based on 70°F and 50% relative humidity. Allow more time at cooler temperatures. Dries to touch in 30 minutes, dry to handle, in 1 hour, and may be recoated after 2-4 hours.

CLEAN-UP

When finished spraying, clear valve by turning can upside down and pushing spray button for 5 seconds. Clean up wet paint with soap and water. For dried paint, use xylene or mineral spirits. Properly discard empty container. Do not burn or place aerosols in home trash compactor.

CLOGGING

If valve clogs, twist and pull off spray tip and rinse it in warm water. For dried paint, rinse in a solvent such as xylene or mineral spirits. Do not stick pin or other objects into the stem.

TECHNICAL DATA

AQUA WATER-BASED AEROSOL

PHYSICAL PROPERTIES

		AQUA WATER-BASED AEROSOL
Resin Type		Acrylic
Pigment Type		Varies with Color
Solvents		Acetone, Di-methyl Ether, Water
MIR		1.4 Max
Fill Weight		12 ounces
Recommended Dry Film Thickness (DFT) per Coat		1.0-2.0 mils
Practical Coverage at Recommended DFT (assumes 15% material loss)		10-12 sq. ft./can (0.9-1.09 m^2/can)
Dry Times at 77°F (25°C) and 50% Relative Humidity	**Touch**	30 minutes
	Handle	2 hours
	Recoat	Within 1 hour or after 48 hours
	Fully Dry	24 hours
Shelf Life		5 years
Flash Point		-156ºF (-104ºC)
Safety Information		For additional information, see MSDS.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.

RUST-OLEUM BRANDS

Rust-Oleum Corporation
11 Hawthorn Parkway
Vernon Hills, Illinois 60061
An RPM Company

Phone: 877•385•8155
www.rustoleum.com

Form: CS2143
Rev.: 022213