AUTOMOTIVE CALIPER CLEANER

DESCRIPTION AND USES

Rust-Oleum® Caliper Cleaner removes contaminants from brake calipers and drums such as brake fluid, grease, and oil. Use prior to painting calipers with Rust-Oleum® Caliper Paint.

PRODUCTS

251597 Caliper Cleaner

PAINTING APPLICATION

PAINTING CONDITIONS

Use outdoors or in a well ventilated area such as an open garage. Use when temperature is between 50°F and 90°F (10-32°C). Avoid spraying in very windy and dusty conditions. Cover surrounding area to protect from spray mist.

SURFACE PREPARATION

Brake dust may contain asbestos. Remove all loose brake dust with an enclosed cylinder/HEPA vacuum. To reduce exposure to air-borne asbestos fibers, do not use Caliper Cleaner to remove dry or loose dirt.

PRODUCT APPLICATION (cont.)

APPLICATION

Shake can vigorously for one minute. Shake often during use. Hold can 10-16òfrom the surface and spray in a steady back-and-forth motion and allow to run off or wipe dry with a clean cloth. Repeat as necessary for areas with heavy deposits. Do not apply to brake linings, painted surfaces, plastic, or parts made of rubber. Do not use near open flame.

CLEAN-UP

Properly discard empty container in trash container. Do not burn or place in home trash compactor.

CLOGGING

If the valve clogs, twist and pull off spray tip and rinse in a solvent such as mineral spirits. Do not insert any object into can valve opening.

TECHNICAL DATA

AUTOMOTIVE CALIPER CLEANER

PHYSICAL PROPERTIES

		CALIPER CLEANER
Resin Type		-
Solvent Type		Blend of acetone and aromatic hydrocarbons
MIR		1.90 Max
Fill Weight		11 ounces
Practical Coverage at Recommended DFT		4-8 calipers/can
Shelf Life		5 years
Safety Information	**Flash Point**	-156°F (-104°C)
	Contains	Lead free
	Warning!	**FOR ADDITIONAL INFORMATION, SEE MSDS.**

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.

RUST-OLEUM BRANDS

Rust-Oleum Corporation
11 Hawthorn Parkway
Vernon Hills, Illinois 60061
An RPM Company

Phone: 877•385•8155
www.rustoleum.com

Form: CS1477
Rev.: 092812