AUTOMOTIVE LACQUER THINNER

DESCRIPTION AND USES

Rust-Oleum® Lacquer Thinner is a high-solvency thinner effective for diluting lacquer-based finishes. It is also excellent for cleaning spray guns immediately after use to keep them in top condition. Carefully read all directions, notes and cautions prior to use.

PRODUCTS

SKU	Description
253309	Lacquer Thinner (Gallon)

PRODUCT APPLICATION

INSTRUCTIONS

Use as a thinner when recommended by the product manufacturer. Always follow the paint manufacturer's instructions for proper reduction ratios. Do not use more than recommended. Protect hands with solvent-resistant gloves and eyes with safety glasses. Most automotive finishes require a specific thinner for use within certain temperature ranges. Rust-Oleum Lacquer Thinner has a medium rate of drying when used within mid-range temperature conditions

PHYSICAL PROPERTIES

Physical Properties		LACQUER THINNER
Composition		Blend of Acetone, Methanol and Toluene
Weight	Per Gallon	6.73 lbs.
	Per Liter	0.80 kg
VOC		300 g/l (2.50 lbs./gal.)
Shelf Life		5 years
Flash Point		-4°F (-20°C)
Safety Information		For additional information, see MSDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.

RUST-OLEUM BRANDS

Rust-Oleum Corporation
11 Hawthorn Parkway
Vernon Hills, Illinois 60061

Phone: 877-385-8155
www.rustoleum.com

Form: GDH-658
Rev: 012215