



**AUTOMOTIVE
WAX & TAR REMOVER**

DESCRIPTION AND USES

Rust-Oleum® Wax & Tar Remover is an effective, fast-acting remover for many automotive surfaces, including metal, plastic and fiberglass. It should be used prior to sanding to prolong the life of sandpaper and again after sanding as a clean-up agent prior to applying top coats. Wax & Tar Remover removes old wax build-up before re-application of new wax to promote an even, mirror-like finish. It is also great for removing grease, silicone and road film.

PRODUCTS

13.5-ounce Spray	Description
251567	Wax & Tar Remover

PRODUCT APPLICATION

APPLICATION

Protect hands with solvent-resistant gloves and eyes with chemical splash goggles.

Hold can in an upright position approximately 8-12" from surface with arrow on button pointed away from you. Apply a liberal coat and allow to stand for 1 minute and wipe dry with a clean lint-free cloth. Turn cloth frequently to ensure a clean side contacts surface. Replace cloth as necessary.

NOTE: Works on most automotive metals, plastics and fiberglass. This product may not be compatible with all surfaces and all conditions surrounding application. Before applying to any surface, always test product in a small inconspicuous area to ensure no damage will result. Do not use on freshly painted surfaces. Ensure paint has cured in accordance with paint manufacturer's instructions. When using between paint coats, always follow the paint manufacturer's instructions regarding cure times. Do not use on metal or plastic surfaces that are hot to the touch. For best results, apply at temperatures between 65-90°F (18-32°C) and avoid direct sunlight or strong breezes.



TECHNICAL DATA

AUTOMOTIVE WAX & TAR REMOVER

Physical Properties	Wax & Tar Remover
Solvents	Aliphatic and Aromatic Hydrocarbons
MIR	1.6 Max
Fill Weight	13.5 oz.
Shelf Life	5 years
Flash Point	-156°F (-104°C)
Safety Information	For additional information, see MSDS.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.