



Rust-Oleum® Camouflage Paint

ITEM NUMBERS	#248664 Olive, #248661 Khaki, #248662 Black, #248663 Brown
DESCRIPTION	A non-reflective enamel used to simulate a camouflage pattern on hunting and sporting equipment.
USES	For Ideal for use on vehicles, tree stands, decoys, blinds, boats and equipment
APPEARANCE	Dries to an ultra flat sheen. Available in Olive, Khaki, Black and Brown
PACKAGING	Available in a 12 oz. aerosol spray can. All Camouflage Paint products feature an Any-Angle Spray system that lets you cover hard to reach places, even if the can is sprayed upside-down and also feature a Comfort Tip spray nozzle to eliminate finger fatigue.
SURFACE PREPARATION	<p>(See directions on can for more details)</p> <p>Remove loose paint and rust with a wire brush or sandpaper. Lightly sand glossy surfaces. Clean the surface with soap and water, rinse and let dry. Cleaning is recommended before and after wire brushing or sanding. The use of a Rust-Oleum® Primer will provide additional adhesion and hiding and is especially recommended for bare wood and metal.</p>
MIXING	Shake can vigorously for one minute after mixing ball begins to rattle. Shake the can often during use.
APPLICATION	Use outdoors or in a well-ventilated area such as an open garage. Use when temperature is between 50°F (10°C) and 90°F (32°C) and humidity is below 85% to ensure proper drying. Avoid spraying in very windy, dusty conditions. Cover surrounding area to protect from spray mist. Hold the can 10-12" from the surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can the same distance from the surface. Keep the can in motion while spraying. Apply 2 or more light coats a few minutes apart. For a real life pattern, use leaves and twigs as stencils. Apply a base coat of color. Lay the leaves and twigs randomly over the object you are painting. Spray over the items using three or more colors. Items painted with Camouflage should not be immersed in water for extended periods of time.

PHYSICAL PROPERTIES (Calculated values, may vary slightly from the actual manufactured material)

RESIN TYPE	ACRYLIC ALKYD
SOLVENT TYPE:	KETONE/AROMATIC
VOC (Volatile Organic Compounds)	1.20 MIR MAX
SOLIDS BY WEIGHT	18.8%

SOLIDS BY VOLUME	7.7%
RECOMMENDED DRY FILM THICKNESS PER COAT	1.0
WET FILM TO ACHIEVE DFT	3 - 4
PRACTICAL COVERAGE @ RECOMMENDED DFT	8 -12 SQUARE FEET
DRY TIMES @70° - 80°F (21° - 27° C) AND 50%RH TACK FREE	30 MINS
SHELF LIFE	5 YEARS

SAFETY (For additional information, see MSDS)

FLASHPOINT	-156F
LEAD-FREE	

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.

RUST-OLEUM CORPORATION • 11 HAWTHORN PARKWAY • VERNON HILLS, ILLINOIS 60061 • TELEPHONE: 888-683-5667