EPOXYSHIELD® ANTI-SKID ADDITIVE

DESCRIPTION AND USES

EPOXYShield® Anti-Skid Additive is an aluminum oxide based anti-skid additive designed to provide skid resistance when added to epoxy, latex or oil based paints or stains for concrete, wood, metal or fiberglass. Anti-Skid Additive will not change the performance or properties of the coatings when added at the recommended level.

PRODUCTS

214393 Anti-Skid Additive

APPEARANCE

Sand-like particles.

PACKAGING

8 ounce carton (227 grams)

PRODUCT APPLICATION

MIXING

For one part floor coatings: Add one package for each gallon of coating just prior to application. Pour the additive in slowly, while stirring and mix thoroughly until the additive is evenly dispersed.

For two part floor coatings: Premix both components to re-disperse any settled particles, then add the activator to the base. If there is an induction time for the product, allow the coating to stand the recommended amount of time. Then pour the additive in slowly, while stirring and mix thoroughly until the additive is evenly dispersed.

For concrete stains: A clear coat must be applied to anchor the anti-skid additive.

APPLICATION

Apply the coating as normal. Remix the paint in the can periodically to ensure that any settled Anti-Skid Additive is reincorporated into the coating. If applying more than one coat of paint, mix the Epoxy Shield Anti-Skid Additive into the final coat only.

Form: 5042790
Rev.: 030612

EPOXYSHIELD® ANTI-SKID ADDITIVE

PHYSICAL PROPERTIES

		ANTI-SKID ADDITIVE
Solvents		Aluminum Oxide
Solids	**By Weight**	100%
	By Volume	100%
Solvents		None
Shelf Life		Unlimited
Safety Information	**Flash Point**	—
	Contains	—
	Warning!	**FOR ADDITIONAL INFORMATION, SEE MSDS.**

Calculated values may vary slightly from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.

RUST-OLEUM BRANDS

Rust-Oleum Corporation
11 Hawthorn Parkway
Vernon Hills, Illinois 60061
An RPM Company

Phone: 877•385•8155
www.rustoleum.com/industrial

Form: 5042790
Rev.: 030612