EPOXYSHIELD® HEAVY DUTY DEGREASER

DESCRIPTION AND USES

EPOXYShield® Heavy Duty Degreaser is formulated to clean grease and oil stains on concrete surfaces prior to painting, staining, and sealing. Heavy Duty Degreaser is ideal for use on garage floors, basements, concrete driveways, sidewalks, porches, patios, and stairs.

PRODUCTS

214382 Heavy Duty Degreaser

PACKAGING

1 quart plastic bottle

PRODUCT APPLICATION

SURFACE PREPARATION

Wipe up excess oil and grease spills. Scrape and sweep away dirt and loose contaminants on surface.

PRODUCT APPLICATION (cont.)

MIXING

Use EPOXYShield® Heavy Duty Degreaser at full strength to clean tough stains. Dilute 1:4 (1 quart [32 oz.] Degreaser in 1 gallon [128 oz.] of water) for general purpose cleaning. To keep your painted floor looking great, dilute 1:16 (1 cup [8 oz.] Degreaser in 1 gallon [128 oz.] of water). Stir diluted solution thoroughly. Avoid splashing.

APPLICATION

Wet the surface first by spraying with a garden hose. Apply the product full strength for tough stains or diluted for general purpose cleaning on bare concrete or painted floors. Thoroughly scrub the surface with a stiff bristle brush or broom. Wait 10-15 minutes to allow the Degreaser to lift stains from the surface. Wipe up excess Degreaser with rags or towels to keep the contaminants from spreading. Rinse thoroughly with fresh water. Repeat applications may be necessary for difficult stains. Remove excess water with a squeegee or mop.

Storage and Disposal

Store at room temperature. Keep container closed when not in use. Dispose of container and/or unused contents in accordance with local, state, and federal regulations. Protect from freezing.

EPOXYSHIELD® HEAVY DUTY DEGREASER

PHYSICAL PROPERTIES

	HEAVY DUTY DEGREASER
Composition	Surfactants and Water
Solids by Weight	13%
Solvents	Glycol Ether and Water
Shelf Life	5 years
pH (as supplied)	13+
Flash Point	>200ºF (93ºF)
Safety	For additional information, see MSDS
NOTE:	Calculated values may vary slightly from the actual manufactured material.

Calculated values may vary slightly from the actual manufactured material.
*Activated material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.

RUST-OLEUM BRANDS

Rust-Oleum Corporation
11 Hawthorn Parkway
Vernon Hills, Illinois 60061
An RPM Company

Phone: 877•385•8155
www.rustoleum.com/industrial

Form: CS685
Rev.: 032612