# CAMOUFLAGE Sprays

| | |
|---|---|
| DESCRIPTION | A flat, non-reflective spray paint. Can be used on wood, metal, and other surfaces to disguise or break up the outlines of items to blend in with different terrains. These durable paints are suitable for outdoor use and resist chipping, cracking and peeling. Not for use on galvanized surfaces. |
| APPEARANCE | Flat |
| PACKAGING | 12 oz cans |
| SURFACE PREPARATION | Remove all dirt, grease, oil, salt or other contaminants by washing the surface with detergent or other suitable cleaner. Rinse thoroughly with fresh water and allow to fully dry.<br><br>Scrape and wire brush or power tool clean to remove loose rust, scale, and deteriorated coatings. Scarify previously painted coatings or smooth surfaces to promote adhesion. Test for compatibility with existing coating.<br><br>Aerosol painting produces overspray that will travel. Protect surrounding area, clothing and skin from overspray. |
| APPLICATION | Apply only when air and surface temperatures are above 50°F (10°C) and humidity is less than 85% to ensure proper drying. Use outdoors or in areas with good ventilation.<br><br>Apply a base coat of one color first. Then use leaves and twigs as stencils; lay them on the surface to make a random pattern. Then use three or more colors to paint stripes and patterns over the leaves and twigs.<br><br>Do not use near open flame |

PHYSICAL PROPERTIES (Calculated values are shown and may vary slightly from the actual manufactured material)

| | |
|---|---|
| RESIN TYPE | Acrylic Modified Alkyd. |
| SOLVENTS | Xylene, Acetone, Toluene |
| VOLATILE ORGANIC COMPOUNDS | Maximum 60% |
| PRACTICAL COVERAGE @ Recommended DFT | Approximately 6 to 7 sq. ft./can (.54-.63 $M^2$/can) |
| DRY TIMES @ 70°F (21°C) and 50% RH | (Lower temperatures or higher humidity will extend dry times)<br>Tack Free 20 minutes<br>Handle 1 hour<br>Recoat Within 1 hour or after 24 hours. |
| DRY HEAT RESISTANCE | 200°F (94° C) |
| SHELF LIFE | 5 Years |