FARM EQUIPMENT Brush-On

DESCRIPTION	Oil modified alkyds with good rust prevention when applied directly to metal. They also offer excellent coverage, chip resistance and color retention. For use on tractors, trailers, trucks, farm implements, lawn mowers and other machinery and equipment.
APPEARANCE	Available in bright durable finishes in a range of original equipment gloss colors.
PACKAGING	Quarts and gallons
RECOMMENDED PRIMERS	For longer lasting protection, use a STOPS RUST® primer first. 7769 Rusty Metal Primer (Red) . For use on heavily rusted metal. 7780 Clean Metal Primer (White). For use on bare or lightly rusted metal.
SURFACE PREPARATION	Remove loose paint and rust with a wire brush or sandpaper. Lightly sand glossy surfaces. Clean surface with soap and water. Rinse thoroughly with fresh water and allow to fully dry.
APPLICATION	Stir thoroughly. Thin material, only if necessary, with mineral spirits. For brush or roller application thin no more than 5%. Do not thin with gasoline, lacquer thinner or turpentine. Apply using a good quality brush, roller, or spray gun. Apply when air and surfaces temperatures are above 50ºF (10ºC).
SHELF LIFE	5 years
CLEAN-UP	Clean brush, roller and other tools with mineral spirits.

PHYSICAL PROPERTIES (Calculated values are shown and may vary slightly from the actual manufactured material)

RESIN TYPE	Oil Modified Alkyd
SOLVENTS	Mineral Spirits
DRY HEAT RESISTANCE	200° F (93º C)
DRY TIMES @ 70º F (21º C) AND 50% RH	Touch: 2 – 4 hours Handle: 5 – 9 hours Recoat: 24 hours Allow more time at cooler temperatures.
SHELF LIFE	5 years
VOLATILE ORGANIC COMPOUND	Exempt – Small size.