FLUORESCENT Sprays

DESCRIPTION	Indoor/Outdoor bright neon colors provide high visibility for a variety of surfaces. Ideal for crafts, color-coding, marking, and more.
APPEARANCE	Flat
PACKAGING	11 oz. can
RECOMMENDED PRIMER	No primer recommended, however using white as a background makes fluorescent appear more brilliant.
SURFACE PREPARATION	Remove all dirt, grease, or other contaminants by washing the surface with detergent or other suitable cleaner. Rinse thoroughly with fresh water and allow to fully dry. Scrape and wire brush or power tool clean to remove loose rust, scale, and deteriorated coatings. Scarify previously painted coatings or smooth surfaces to promote adhesion. Test for compatibility with existing coating.
APPLICATION	Apply only when air and surface temperatures are above 50°F (10°C) to ensure proper drying. Use in properly ventilated area. Spraying can produce a fog that will travel. Protect surrounding area, clothing and skin from overspray. Do not use near open flame.
CLEANUP	When finished spraying, clear spray valve by turning can upside down and pushing spray button for 5 seconds. If valve clogs, twist and pull off spray tip and rinse it in a solvent such as mineral spirits. Do not stick a pin or other object into the stem. Throw away empty can in trash pickup. Do not burn or place in home trash compactor.

PHYSICAL PROPERTIES (Calculated values are shown and may vary slightly from the actual manufactured material)

RESIN TYPE	Modified Acrylic Lacquer	
SOLVENTS	Xylene, Toluene, Acetone, Hexane	
VOLATILE ORGANIC COMPOUNDS	<60% vol. by wt.	
PRACTICAL COVERAGE	Approximately 10-12 sq. ft./can	
DRY TIMES @ 70°F (21°C) and 50% RH	Tack Free:	15 minutes
	Handle:	30 minutes
	Recoat:	Anytime
DRY HEAT RESISTANCE	200°F (94° C)	
SHELF LIFE	5 Years	