

METALLIC Sprays

DESCRIPTION	Brilliant colors combined with metal flakes for a bright metallic look. For use indoors on surfaces such as wood or metal. Note: Metal flakes may rub off if handled.
APPEARANCE	Shiny metallic
PACKAGING	11-oz. can
RECOMMENDED PRIMER	None
SURFACE PREPARATION	<p>Remove all dirt, grease, oil, salt or other contaminants by washing the surface with detergent or other suitable cleaner. Rinse thoroughly with fresh water and allow to fully dry.</p> <p>Scrape and wire brush or power tool clean to remove loose rust, scale, and deteriorated coatings. Scarify previously painted coatings or smooth surfaces to promote adhesion. Test for compatibility with existing coating.</p> <p>Use in properly ventilated area. Spraying can produce a fog that will travel. Protect surrounding area, clothing and skin from overspray.</p>
APPLICATION	<p>Apply only when air and surface temperatures are above 50°F (10° C) and humidity is less than 85% to ensure proper drying. Use outdoors or in areas with good ventilation.</p> <p>Apply two or more light coats a few minutes apart.</p>
CLEANUP	When finished spraying, clear spray valve by turning can upside down and pushing spray button for 5 seconds. If valve clogs, twist and pull off spray tip and rinse it in a solvent such as mineral spirits. Do not stick a pin or other object into the stem. Throw away empty can in trash pickup. Do not burn or place in home trash compactor.

PHYSICAL PROPERTIES (Calculated values are shown and may vary slightly from the actual manufactured material)

RESIN TYPE	Solvent Acrylic
SOLVENTS	Xylene, Acetone, Toluene
VOLATILE ORGANIC COMPOUNDS	< 80% vol. by wt.
PRACTICAL COVERAGE	Approximately 10-12 sq. ft./can
DRY TIMES @ 70°F (21°C) and 50% RH	Tack Free: 20 minutes Handle: 30 minutes Recoat: Anytime (Lower temperatures or higher humidity will extend dry times)
DRY HEAT RESISTANCE	200°F (94° C)
SHELF LIFE	5 Years