

• TRUSTED QUALITY SINCE 1921 •

RUST-OLEUM®
SPECIALTY

**SPECIALTY
REFLECTIVE SPRAY**

DESCRIPTION AND USES

Rust-Oleum® Specialty Reflective Spray is a semi-transparent finish that reflects light for nighttime visibility and safety. Surfaces painted with Reflective Finish appear bright when headlights illuminate it. Ideal for use on mailboxes, gates, trash cans, light posts, bicycles, driveway rocks and more.

PRODUCTS

FINISHES

214944 Reflective Spray

PRODUCT APPLICATION

PAINTING CONDITIONS

Use outdoors or in a well ventilated area such as an open garage. Use when temperature is between 50°F (10°C) and 90°F (32°C) and humidity is below 65% to ensure proper drying. Do not apply to surfaces, when heated, exceed 200°F (93°C). Do not apply to galvanized steel. Avoid spraying in very windy and dusty conditions. Cover surrounding area to protect from spray mist.

SURFACE PREPARATION

Remove all dirt, grease, oil, salt and chemical contaminants by washing the surface with a commercial detergent, or other suitable cleaning method. Rinse with fresh water and allow to thoroughly dry.

PRODUCT APPLICATION

APPLICATION

Shake can vigorously for one minute after the mixing ball begins to rattle. If mixing ball fails to rattle DO NOT STRIKE CAN. Contact Rust-Oleum. IMPORTANT! Shake can approximately 4 seconds for every 15 seconds of use. Hold can upright 10-16" from surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Apply 2-3 light coats 1-2 minutes apart. Keep the can the same distance from the surface and in motion while spraying. DO NOT APPLY HEAVY COATS THAT LOOK WET. The effect works best when light coats are applied.

DRY & RECOAT TIMES

Dry and recoat times are based on 70°F (21°C) and 50% relative humidity. Allow more time at cooler temperatures. The finish dries to the touch in 1-3 hours. Allow 5-9 hours to handle and 24 hours to dry fully.

CLEAN-UP

Clean valve immediately after use by turning can upside down and depressing spray button for 3-5 seconds (some paint will be sprayed out, so be careful to not inadvertently spray yourself or other objects). Clean-up wet paint with xylene or mineral spirits. Properly discard empty container. Do not burn or place in home trash compactor.

CLOGGING

If the valve clogs, twist and pull off spray tip and rinse in a solvent such as mineral spirits. Do not insert any object into can valve opening.

PHYSICAL PROPERTIES

		REFLECTIVE SPRAY
Resin Type		Modified Alkyd
MIR		1.4 Max
Fill Weight		10 oz.
Solvents		Acetone, Aromatic hydrocarbons, Toluene
Recommended Dry Film Thickness (DFT) per coat		1.0-2.0 mils
Practical Coverage at Recommended DFT (assumes 15% material loss)		4.5 sq. ft./can (0.37-0.46 m ² /can)
Dry Times at 77°F (25°C) and 50% Relative Humidity	Touch	1-3 hours
	Handle	5-9 hours
	Fully Dry	24 hours
Dry Heat Resistance		200°F (93°C)
Shelf Life		5 years
Safety Information	Flash Point	-156°F (-144°C)
	Warning!	For additional information, see MSDS.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.