

COUNTERTOP PAINT

DESCRIPTION	Paint designed to renew and restore laminate countertops, cabinets and furniture. This coating resists chemicals, moisture and scratches. It contains antimicrobial protection that inhibits the growth of mold, mildew and other odor or stain causing microbes. It adheres to laminate as well as vinyl, wood and metal. Not for use on floors, granite, marble, tile or concrete.
APPEARANCE	Satin Off-White Tint Base, 246068, that is tintable to 16 satin colors: Ivory, Canvas, Haystack, Wheat, Taupe, Earth, Cobblestone, Putty, Light Ash, Gray Mist, Pewter, Palest Blue, Coastal Blue, Meadow, Olive, Rosemary.
RECOMMENDED PRIMERS	If painting on laminate or vinyl surface, no primer is needed. For bare metal or bare wood surfaces, a Rust-Oleum primer is recommended for superior adhesion and hiding. Please consult the Rust-Oleum Web Site for appropriate primer.
FILL WEIGHT	Net 29 fluid ounces (824 mL)
SURFACE PREPARATION	Remove loose paint and rust with a wire brush or sandpaper. Lightly sand glossy surfaces. Clean with soap and water, rinse and let dry.
APPLICATION	<p>Use when in a well ventilated area where temperature is between 50°F(10°C) and 90°F(32°C) and humidity is below 85% to ensure proper drying. Do not apply to surfaces that, when heated, exceed 200°F(93°C) or galvanized metal. Stir thoroughly. If thinning is necessary, thin material only with xylene. Thin no more than 5%. Use a foam roller that is designed to give a smooth finish or a spray gun. Use a high quality brush with flagged (split) ends for smaller areas. For best results, use the roller to paint the entire surface and use the brush for hard-to-reach or smaller areas. Allow 3 DAYS for surface to dry.</p> <p><i>Note on Care of Painted Surface:</i> Clean painted surface with a damp non-abrasive cloth, mild detergent or mild household cleaner. Do not scrub with abrasive cleaners, steel wool, sandpaper or scouring pads. As with most manufactured laminate surfaces, this paint surface will remain durable with proper use and care. Use a trivet or other protective material underneath all hot cookware and other heated objects. Use cutting boards or other protective surfaces when preparing food. Heavy pounding, knives or other sharp utensils may scratch the surface.</p>
CLEAN-UP	Clean brush and other tools with xylene.

PHYSICAL PROPERTIES (Calculated values are shown and may vary slightly from the actual manufactured material)

RESIN TYPE	Alkyd Enamel
SOLVENTS	Xylene and Aromatic Hydrocarbon
PRACTICAL COVERAGE	25 linear feet of an average countertop
DRY TIMES @77°F (25°C) and 50% RH	
DRY TO TOUCH	1-2 hours
HANDLE	4-6 hours
RECOAT	Within 1 hour or after 24 hours.
VOLATILE ORGANIC COMPOUND	495 gm/l
SHELF LIFE	5 Years

SAFETY

FLASH POINT
LEAD FREE

81⁰F (27⁰C)

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.

RUST-OLEUM CORPORATION • 11 HAWTHORN PARKWAY • VERNON HILLS, ILLINOIS 60061 • TELEPHONE: 888-683-5667

An  Company

Published 12/08