

• TRUSTED QUALITY SINCE 1921 •

**RUST-OLEUM®**  
SPECIALTY

**SPECIALTY  
FROSTED GLASS SPRAYS**

**DESCRIPTION AND USES**

Rust-Oleum® Frosted Glass Spray creates an etched glass appearance but permits light to transmit through the painted surface. It is designed for use on glass doors, windows, skylights, shower doors, and greenhouses. For a decorative effect, use a stencil to create an etched look on mirrors, shower door exteriors, glass accessories, and more.

**PRODUCTS**

**FINISHES**

1903830      Frosted Glass

**PRODUCT APPLICATION**

**PAINTING CONDITIONS**

Use outdoors or in a well ventilated area such as an open garage. Use when temperature is between 50°F (10°C) and 90°F (32°C) and humidity is below 65% to ensure proper drying. Do not apply to surfaces, when heated, exceed 200°F (93°C). or surfaces that are exposed to repeated or continuous water contact, such as the inside of shower doors. Avoid spraying in very windy and dusty conditions. Cover surrounding area to protect from spray mist.

**SURFACE PREPARATION**

Remove all dirt, grease, oil, salt and chemical contaminants by washing the surface with a commercial detergent, or other suitable cleaning method. Rinse with fresh water and allow to thoroughly dry.

**PRODUCT APPLICATION (cont.)**

**APPLICATION**

Shake can vigorously for one minute after the mixing ball begins to rattle. If mixing ball fails to rattle **DO NOT STRIKE CAN**. Contact Rust-Oleum. Shake often during use. Hold can upright 10-16" from surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can in motion while spraying. Apply two or more wet coats a few minutes apart for best appearance. A wet coat should appear shiny as it is applied to the surface. **WAIT 10 MINUTES FOR FROST EFFECT**. Not for outdoor use. **Do not use near open flame.**

**DRY & RECOAT TIMES**

Dry and recoat times are based on 70°F and 50% relative humidity. Allow more time at cooler temperatures. Dries completely in 5-10 minutes. May recoat anytime.

**CLEAN-UP**

When finished spraying, clear spray valve by turning can upside down and depressing spray button for 3-5 seconds (some paint will be sprayed out, so be careful to not inadvertently spray yourself or other objects). Clean-up wet paint with xylene or mineral spirits. Properly discard empty container. Do not burn or place in home trash compactor.

**CLOGGING**

If the valve clogs, twist and pull off spray tip and rinse in a solvent such as mineral spirits. Do not insert any object into can valve opening.

**PHYSICAL PROPERTIES**

		<b>FROSTED GLASS</b>
<b>Resin Type</b>		Acrylic Lacquer
<b>Pigment Type</b>		Proprietary
<b>MIR</b>		1.4 Max
<b>Fill Weight</b>		11 oz.
<b>Solvents</b>		Toluene and Xylene
<b>Recommended Dry Film Thickness (DFT) per coat</b>		1.0-2.0 mils
<b>Practical Coverage at Recommended DFT (assumes 15% material loss)</b>		7 sq. ft./can (0.63 m <sup>2</sup> /can)
<b>Dry Times at 77°F (25°C) and 50% Relative Humidity</b>	<b>Touch</b>	5 minutes
	<b>Fully Dry</b>	10 minutes
	<b>Recoat</b>	Anytime
<b>Dry Heat Resistance</b>		200°F (94°C)
<b>Shelf Life</b>		5 years
<b>Safety Information</b>	<b>Flash Point</b>	-156°F (-144°C)
	<b>Contains</b>	Lead-free
	<b>Warning!</b>	<b>For additional information, see MSDS.</b>

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.