• TRUSTED QUALITY SINCE 1921 •
RUST-OLEUM®
STOPS RUST®

STOPS RUST BRIGHT COAT METALLIC SPRAYS

DESCRIPTION AND USES

Rust-Oleum® Stops Rust® Bright Coat Metallic Sprays are designed to provide a durable protective coating with excellent resistance to rust, and excellent resistance to abrasion, fading, chipping, and dulling. These sprays apply easily, provide excellent coverage and dry fast to a tough attractive finish. Aluminum is appropriate for outdoor metal surfaces when primed first. Gold, Chrome, and Bronze should be used indoors as they will tarnish if placed outdoors. These sprays feature a comfort tip with a wider finger pad to reduce fatigue caused by continuous spraying and the any-angle tip which allows you to spray at any angle.

PRODUCTS

FINISHES

7710830	Gold
7713830	Dark Bronze
7715830	Aluminum
7718830	Gloss Chrome
V7715830	VOC Aluminum

PRODUCT APPLICATION

PAINTING CONDITIONS

Use outdoors or in a well ventilated area such as an open garage. Use when temperature is between 50°F (10°C) and 90°F (32°C) and humidity is below 85% to ensure proper drying. Do not apply to surfaces, when heated, exceed 200°F (93°C). Avoid spraying in very windy and dusty conditions. Cover surrounding area to protect from spray mist.

SURFACE PREPARATION

Remove all dirt, grease, oil, salt and chemical contaminants by washing the surface with a commercial detergent, or other suitable cleaning method. Rinse with fresh water and allow to thoroughly dry. Remove loose paint and rust with a wire brush or sandpaper. Previously coated surfaces must be sound and in good condition. Smooth, hard, or glossy finishes should be scarified by sanding to create a surface profile. WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the U.S.EPA/Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

PRODUCT APPLICATION (cont.)

PRIMING

Use of a Rust-Oleum® primer provides added corrosion protection, excellent adhesion and hiding and is especially recommended for bare wood and metal. The following primers are recommended.

7769 Rusty Metal Primer
7780 Clean Metal Primer

PAINTING

Shake can vigorously for one minute after the mixing ball begins to rattle. Shake often during use. Hold can upright 12-16" from surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can the same distance from the surface. Keep the can in motion while spraying. Apply two or more light coats a few minutes apart to avoid drips and runs. Do not use near open flame.

DRY & RECOAT

Dry and recoat times are based on 70°F and 50% relative humidity. Allow more time at cooler temperatures. Dries to touch in 1 hour and primers may be top coated immediately. Apply a second coat within 1 hour or after 48 hours. **A clear coat finish is not recommended.**

CLEAN-UP

Wipe off tip before storing. Clean-up wet paint with xylene or mineral spirits. Properly discard empty container. Do not burn or place in home trash compactor.

CLOGGING

If the valve clogs, twist and pull off spray tip and rinse in a solvent such as mineral spirits. Do not insert any object into can valve opening.

Form: 5033790
Rev.: 072211

TECHNICAL DATA

STOPS RUST BRIGHT COAT METALLIC SPRAYS

PHYSICAL PROPERTIES

		METALLIC
Resin Type		Solvent Acrylic
Pigment Type		Varies with Color
MIR		1.9 Max
Fill Weight		11 ounces
Solvents		Acetone, Toluene, Xylene
Recommended Dry Film Thickness (DFT) Per Coat		1.0-2.0 mils (25-50µ)
Practical Coverage at Recommended DFT		10-12 sq.ft. /qt. (0.25-0.30 m^2/l)
Dry Times at 77°F (25°C) and 50% Rel. Hum.	**Tack-free**	1 hour
	Handle	1 hour
	Recoat	Before 1 hour or after 48 hours
Dry Heat Resistance		200°F (94°C)
Shelf Life		5 years
Safety Information	**Flash Point**	-156°F (-144°C)
	Contains	Lead-free
	Warning!	**FOR ADDITIONAL INFORMATION, SEE MSDS.**

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.

RUST-OLEUM BRANDS

Rust-Oleum Corporation
11 Hawthorn Parkway
Vernon Hills, Illinois 60061
An RPM Company

Phone: 888•683•5667
www.rustoleum.com

Form: 5033790
Rev.: 072211