



STOPS RUST RUST STRIPPER

DESCRIPTION AND USES

Rust-Oleum® Rust Stripper is an acid based formula that safely strips metal clean. Rust Stripper is a quick and easy first step to restoring metal surfaces to the original finish. It is suitable for use on tools, automobiles, patio furniture, iron railings and doors, mailboxes, bicycles, swing sets, lawn equipment and most other metal, steel, and iron products. **DO NOT** use Rust Stripper on aluminum, chrome or galvanized steel.

PRODUCTS

SKU (8 fl. oz.)	Description
7840490	Rust Stripper

PRODUCT APPLICATION

SURFACE PREPARATION

Wear rubber gloves and safety glasses when using this product. Remove all dirt, grease, oil, salt and chemical contaminants by washing the surface with a commercial detergent, or other suitable cleaning method. Rinse with fresh water and allow to thoroughly dry. Remove all loose rust, scale, and previous coatings with a wire brush, scraper, or putty knife. Power tool clean to remove severe rust and corrosion and deteriorated coatings. **WARNING!** If you scrape, sand or remove old paint from any surface, you may release lead paint dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE; ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

PRODUCT APPLICATION (cont.)

APPLICATION

Use outdoors or in a well ventilated area such as an open garage. Apply when temperature is between 50-90°F (10-32°C) and humidity is below 85% to ensure efficient use of the product. Apply Rust Stripper and spread evenly with a brush. Wait 10 minutes. Rinse with fresh water. Use the enclosed stripper pad to loosen rust from the surface and dry with a clean towel. Repeat as necessary.

Prime and paint the clean metal surface within 24 hours of using Rust Stripper. If a clean metal surface will not be painted, oil the surface immediately. For maximum rust prevention, prime the metal surface with a Rust-Oleum Stops Rust® Primer and apply a Stops Rust® finish coat. Recommended primers include 7769830 Rusty Metal Primer, 7780830 Clean Metal Primer, or one of the automotive primers.

CLEAN-UP

Clean pad and any spills with warm, soapy water while the Rust Stripper is still wet.



TECHNICAL DATA

STOPS RUST STRIPPER

PHYSICAL PROPERTIES

Physical Properties		RUST STRIPPER
Composition		Hydrochloric Acid
Solvent		Water
Weight	Per Gallon	9.8 lbs.
	Per Liter	1.17 kg
Shelf Life		5 years
Flash Point		NA
Warning!		CORROSIVE! CONTAINS HYDROCHLORIC ACID
Safety Information		For additional information, see MSDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Rust-Oleum Corporation
11 Hawthorn Parkway
Vernon Hills, Illinois 60061
An RPM Company

Phone: 877-385-8155
www.rustoleum.com

Form: CS2114
Rev.: 030113