VARATHANE®
ALL PURPOSE WOOD CLEANER

DESCRIPTION AND USES

Varathane® All Purpose Wood Cleaner is a general purpose cleaner designed to remove dirt and grime from all types of finished and unfinished wood surfaces, including laminate. Regular use of this product will help protect and preserve wood and laminate surfaces without the residue of other cleaners.

Varathane All Purpose Wood Cleaner is also suitable for cleaning wood and pre-finished wood floors prior to applying Varathane Wood Refresher.

PRODUCTS

1-Quart	Description
247830	All Purpose Wood Cleaner

PRODUCT APPLICATION

APPLICATION

Furniture **-** Apply Varathane All Purpose Wood Cleaner directly to the furniture surface with a lint-free cloth and then scrub the object thoroughly. Do not thin.

Wood & Laminate Floors **-** Sweep the floor to remove any loose dirt. Apply the cleaner directly to the floor in a “Z” pattern in a 4’ x 4’ area. Spread the cleaner over the surface area with damp mop or damp sponge. Remove any excess cleaner with a foam style mop or sponge. Allow the floor to dry (approximately 30 minutes) before allowing foot traffic across the surface. Apply Varathane Wood Refresher to enhance protection on the floor.

Varathane All Purpose Wood Cleaner will clean laminate floor surfaces, but Varathane No Sanding Prep must be applied prior to using Varathane Wood Refresher.

STORAGE & DISPOSAL

Store at room temperature. Keep container closed when not in use. Dispose of container and/or unused contents in accordance with local, state and federal regulations.

Clean Up

Clean up with soap and water.

TECHNICAL DATA

VARATHANE® ALL PURPOSE WOOD CLEANER

		ALL PURPOSE WOOD CLEANER
Composition		Blend of Surfactants
Pigment Type		NA
Solvents		Water
Volatile Organic Compounds		0 g/l
Practical Coverage at Recommended DFT (assumes 15% material loss)		225 sq.ft./quart
Dry Times at 77°F (25°C) and 50% Relative Humidity	**Touch**	15 minutes
	Foot Traffic	30 minutes
Shelf Life		3 years
Flash Point		>200°F (93°C)
Safety Information		For additional information, see MSDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.

RUST-OLEUM BRANDS

Rust-Oleum Corporation
11 Hawthorn Parkway
Vernon Hills, Illinois 60061
An RPM Company

Phone: 877•385•8155
www.rustoleum.com

Form: RAC-30
Rev.: 013013