WATCO® REJUVENATING OIL

DESCRIPTION AND USES

Watco® Rejuvenating Oil is a special oil designed for the care and restoration of oil-finished woods. Periodic use of Watco Rejuvenating Oil restores beauty to oil-finished wood by removing surface grime and creating a renewed luster and protection. Rejuvenating Oil replenishes dried out wood and leaves a pleasant lemon scent. It is suitable for use on furniture, trim, paneling or any oil-finished wood surface. It is not recommended for floors or exterior surfaces.

PRODUCTS

1-Quart	Description
66041	Rejuvenating Oil

PRODUCT APPLICATION

SURFACE PREPARATION

Watco Rejuvenating Oil will dissolve wax so there is no need to strip waxed wood before applying.

If sanding of the wood surface is required, prepare by sanding in the direction of the grain. Begin with #120 grit sandpaper and progress though #150, #180 and #220 grits. Remove all sanding dust and dirt with a vacuum, tack cloth, or rag dampened with mineral spirits.

WARNING! If you scrape, sand or remove old paint, you may Release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

PRODUCT APPLICATION (cont.)

APPLICATION

Use only when air (ambient) temperature is between 60-90°F (16-32°C) and relative humidity is below 85%. Allow for longer dry times during damp and humid conditions. Gently shake the container to ensure thorough mixing of contents. Do not thin. Apply Rejuvenating Oil with a soft lint-free cloth. Wait 10 minutes and wipe the surface clean and dry with a soft cloth.

To remove minor surface stains and scratches, apply Rejuvenating Oil with fine steel wool or synthetic steel wool in the direction of the wood grain.

WAXING

For a rich, soft satin luster, apply Watco Satin wax for finishing after the oil has been allowed to dry for 72 hours.

CLEAN UP

Use paint thinner or mineral spirits.

WATCO® DANISH OIL

PHYSICAL PROPERTIES

		REJUVENATING OIL
Resin Type		Urethane-modified Linseed Oil
Pigment Type		None
Solvents		Mineral spirits
Weight	**Per Gallon**	7.1 lbs.
	Per Liter	0.85 kg
Solids	**By Weight**	45.0%
	By Volume	40.4%
Volatile Organic Compounds		458 g/l
Recommended Dry Film Thickness (DFT) Per Coat		NA
Wet Film to Achieve DFT (unthinned material)		NA
Theoretical Coverage at 1 mil DFT (25µ)		648 sq.ft./gal.
Practical Coverage at Recommended DFT (assumes 15% material loss)		50-75 sq.ft./quart (Varies with type and porosity of wood)
Dry Times at 77°F (25°C) and 50% Relative Humidity	**Touch**	10 minutes
	Apply Wax	72 hours
Shelf Life		3 years
Flash Point		104°F (40°C)
Safety Information		For additional information, see MSDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.