•TRUSTED QUALITY SINCE 1921•

RUST-OLEUM®

ULTIMATE SPAR VARNISH - SPRAY

DESCRIPTION AND USES

Rust-Oleum® Ultimate Spar Varnish Aerosol provides maximum protection for all your outdoor wood projects. Rust-Oleum Ultimate Spar Varnish Aerosol is specially formulated to provide maximum protection against sun, water, weather, sea spray and chemicals, which can take years off the life of your outdoor wood. It features an advanced spray system that allows you to spray at any angle, even upside down for those hard to reach areas. A comfort grip trigger eliminates finger fatigue cause by continuous spraying. It is ideal for all outdoor projects such as outdoor furniture, doors and window trim.

PRODUCTS

SKU	Description
260346	Spar Varnish Gloss
260347	Spar Varnish Semi-Gloss
260348	Spar Varnish Satin

PRODUCT APPLICATION

Unfinished Surface Preparation: Sand using 150-220 grit sandpaper and remove all sanding dust using a vacuum or a tack cloth. If a filler or putty is used, make sure that it does not contain wax.

Refurbishing existing coating: Existing finished wood may be refurbished without complete removal of the previous coating. The surface must be free from wax, silicones, oils and other contaminants, thoroughly cleaned and abraded before applying Ultimate Polyurethane

Stained or Painted Wood: Follow manufacturer's direction for application of stain or paint. Make certain surface is thoroughly dry before applying Rust-Oleum Ultimate Spar Varnish. Refer to manufacturer's label for dry times. For best results, use Rust-Oleum Ultimate Wood Stains when a stained surface is desired.

SURFACE PREPARATION

Surfaces must be clean, dry, and free from wax, grease and dust. Prepare the wood surface by sanding in the direction of the grain. Begin with #120 grit sandpaper and progress through #150, #180, and #220 grit. Remove all sanding dust with a vacuum or clean lint-free cloth dampened with mineral spirits.

WARNING! If you scrape, sand or remove old paint, you may Release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

PRODUCT APPLICATION (cont.)

APPLICATION

Shake can vigorously before and after use. Use a drop cloth or newspapers to protect surrounding areas from spray mist. Spray light mist coats, holding can 10-12 inches from surface. Move can with a smooth sweeping motion to avoid runs and sags. Several light coats give a better finish than one heavy coat. For hard to reach areas turn the can upside down to spray. Allow finish to dry then re-coat. Dries to the touch in 1 hour; re-coat after 2 hours. Let dry overnight before use. For extra smoothness, sand lightly with fine grit (#220) sandpaper before final coat. For maximum durability, a minimum of 3 coats is recommended.

Not Recommended for: Decks or high traffic areas, siding or rough-sawn surfaces. This product is not intended for interior surfaces with the exception of window trim.

DRY TIMES

Use adequate ventilation at all times. Do not apply in direct sunlight. Apply at temperatures above 55°F or below 90°F. Use care when applying over white or pastel paints or stains as discoloration may occur. Test Rust-Oleum Ultimate Spar Varnish in an inconspicuous area before beginning.

CLEAN UP

Use mineral spirits. Dispose of properly. For guidance on disposal of unused product, contact your local or state government environmental agency.

TECHNICAL DATA

ULTIMATE SPAR VARNISH - SPRAY

		ULTIMATE POLYURETHANE
Resin Type		Alkyd / Polyurethane
Solvents		Acetone / Mineral Spirits
Volatile Organic Compound		MIR 0.73
Practical Coverage at Recommended DFT (assumes 15% material loss)		40 - 50sq.ft./gal.
Dry Times at 70°F (21°C) and 50% Relative Humidity	**Touch**	1 hours
	Recoat	2hours
	Through	16 hours
Shelf Life		5 years
Flash Point		-156°F (104°C)
Safety Information		For additional information, see MSDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.

RUST-OLEUM BRANDS

Rust-Oleum Corporation
11 Hawthorn Parkway
Vernon Hills, Illinois 60061
An RPM Company

Phone: 877•385•8155
www.rustoleum.com

Form:JPB-35
Rev.: 011014