

DIF[®] FAST-ACTING READY-TO-USE LIQUID WALLPAPER STRIPPER

- **Powerful formula works in minutes**
- **Unique liquid clings to vertical surfaces**
- **Only one application needed**
- **Easy to apply with sprayer or roller**
- **Highly effective on all types of wallpaper**
- **Non-toxic, mildly scented, safe to use**

Selection Data

Generic Type – Pre-mixed liquid wallcovering stripper solution.

Recommended Uses

DIF Fast-Acting LIQUID can be used to strip most types of wallpapers that cannot be effectively peeled or dry-stripped from the walls. These include: traditional paper wallpapers, vinyl coated papers, paper-backed vinyl wallpapers, solid vinyl wallpapers, foils, mylars, grasscloth, textiles and even painted wallpapers. (Borders – see section – Removal of wallpaper borders.)

Application Data

Determining Where to Begin Removal

The type of wallpaper will determine where to begin the removal process. Grasp a seam or an edge of the wallpaper and try to peel it off. Remove any layer that will peel off first and then apply DIF Fast-Acting LIQUID to the remaining backing paper or residual adhesive. Stop if attempts to dry strip the existing wallpaper fail or result in damage to the drywall, and refer to the instructions below for removal of specific types of wallpaper.

- **Traditional Paper Wallpaper**

Traditional paper wallpaper is uncoated, porous and will absorb removers readily. No further preparation is necessary before applying DIF Fast-Acting LIQUID.

- **Coated Wallpaper**

If wallpaper is a washable type (generally a standard paper that is coated with a vinyl or acrylic coating) score* the surface using the ZINSSER PaperTiger[®] scoring tool to enhance DIF Fast-Acting LIQUID penetration. Score the wallpaper from the ceiling to the floor, using just enough force to break through the surface of the wallpaper.

- **Painted Wallpaper**

If the wallpaper has been painted over, score the surface thoroughly using the PaperTiger scoring tool.

- **Vinyl Wallpaper**

Most vinyl wallpapers are either peelable (the top layer can be removed, leaving the paper backing behind) or strippable (the entire sheet of wallpaper can be removed, leaving only adhesive residue behind). Always try to peel or strip the wallpaper first and apply DIF Fast-Acting LIQUID to the paper backing or adhesive residue. If the vinyl wallpaper cannot be peeled or stripped off, score the surface thoroughly with the PaperTiger before applying DIF Fast-Acting LIQUID.

- **Foil, Mylars, and Other Sealed Wallpapers**

Thoroughly score the surface with the PaperTiger before applying DIF Fast-Acting LIQUID.

- **Textiles**

If textile has been installed directly over adhesive, simply apply DIF Fast-Acting LIQUID. Some textiles need their surface scored with the PaperTiger.

- **Multiple Layers of Wallpaper**

It may be necessary to remove the wallpaper one layer at a time since multiple layers can resist full penetration of the scoring tool.

*When using the PaperTiger, apply only enough pressure to penetrate the wallpaper to avoid damaging the drywall. The more holes the better. If unsure, test a small area before proceeding.



Application

Before using DIF Fast-Acting LIQUID, protect carpeting, floors, furniture and adjacent areas. For convenience, apply DIF Fast-Acting LIQUID using the refillable 32 oz. spray bottle or the larger gallon with spray nozzle attached. For big projects, apply using a WALWorks® stripper roller or a medium nap (3/8" – 1/2") roller. Pour enough DIF Fast-Acting LIQUID to fill a plastic paint tray or pour multiple containers into a plastic 5-gallon pail, insert a roller grid and load the roller from the pail. Apply enough DIF Fast-Acting LIQUID to leave a thick layer of stripper on surface of the wallpaper. When rolling use slow, steady rolling motions to avoid splattering the stripper. Be sure to apply in corners and tight spots.

Coverage

One gallon of DIF Fast-Acting LIQUID will cover a little over half of a 10' x 12' room with 8' ceiling (approximately 300 square feet or 6 bolts of wallpaper). Note that coverage will vary with porosity of wallpaper and thickness of product application.

Wetting Period

DIF Fast-Acting LIQUID functions much like paint remover, i.e. it must penetrate the wallpaper and loosen the adhesive. Reaction time will vary depending on the type of wallpaper being removed as well as the type of adhesive used. Most wallpaper will be ready for removal 2 – 10 minutes after DIF Fast-Acting LIQUID has been applied. Some types of wallpaper may take longer.

Scraping Off the Wallpaper

Use the ZINSSER Paper Scraper™** to remove loosened wallpaper. Place blade of Paper Scraper at top edge of side of wallpaper section and gently slide underneath wallpaper to separate it from the wall. For stubborn areas, reapply DIF Fast-Acting LIQUID and wait an additional 15 minutes before removing.

Adhesive Removal

Apply DIF Fast-Acting LIQUID and allow to soak until the adhesive is loose and can be sponged or scraped off with the ZINSSER Paper Scraper or a wide putty knife. DIF Fast-Acting LIQUID will remove starch based adhesives, but not non-water soluble vinyl-over-vinyl or border adhesives.

**The ZINSSER Paper Scraper is a tool specially designed to remove loosened wallpaper and old adhesive without gouging or cutting the drywall.

Removal of Wallpaper Borders

Wallpaper borders are frequently installed with a special glue called "border adhesive" or "vinyl-to-vinyl adhesive". This glue is very similar to common white glue (Elmer's® Glue) and cannot be removed with wallpaper removers including DIF Fast-Acting LIQUID. There is no easy way to remove borders installed with these glues. Try to peel off the decorative layer as mentioned earlier, and then start soaking using one of the DIF Wallpaper Strippers. The white glue may soften with long soaking. Scrape off as much of the border and adhesive as possible using a Paper Scraper. After scraping, sand off the remaining portion with 100-grit sandpaper. Expect some wall damage. Spot prime areas with B-I-N® Spray Primer or GARDZ® High Performance Sealer and patch with Ready Patch® Spackling & Patching Compound and sand smooth. Protect porous adjacent surfaces such as popcorn ceilings.

Wall Clean-up

After wallpaper has been removed apply a thin layer of DIF Fast-Acting LIQUID to walls to remove any remaining adhesive. After 10 minutes rinse the surfaces and adjoining areas very well with water. Look to see that all of the stripper solution is removed. Be sure to change rinse water frequently to avoid recontamination of the walls. If there is mildew, use a household mildew cleaner to destroy any mildew that may be present. Rinse walls and allow to dry before painting or installing new wallpaper.

Tool Clean-up

Wash roller, brush, and any trays, pans, or buckets with warm tap water.

Storage/Shelf Life/Disposal

Although DIF Fast-Acting LIQUID has an indefinite shelf life, always keep the container tightly closed and store in a cool, dry place away from direct sunlight or extreme heat. Protect from freezing. The disposal of excess or left over product should conform to local laws regarding water-based products.

Precautions

Persons with sensitive skin should wear rubber gloves when applying this product. Always work with adequate ventilation and remove pets from work area. Avoid prolonged contact of DIF Fast-Acting LIQUID with woodwork, cabinets, countertops, floors etc. as wetting agents may discolor certain finishes.

Caution

Do not take internally. Keep away from children. Close container after each use and keep cap tightly closed during storage. Keep from freezing.

Warranty

DIF Fast-Acting LIQUID is warranted to perform as indicated on the product label if applied according to directions. Label directions are as complete as possible but cannot encompass all conditions, applications and/or surfaces beyond our control. The contents of this container are warranted to be free of defects for 2 years from the date of manufacture. All warranties and guarantees are limited to replacement or refund value of the product used with proof of purchase. No other warranty or guarantee is expressed or implied. If you have a question, check with your dealer or contact Rust-Oleum Corporation, Vernon Hills, IL.

Packaging and Shipping Information

Size	Item No.	Product UPC	Carton Code	Case Dimensions	Case Pack	Case Wt	Case Vol. In.	Pallet Pack	Pallet Size
32 oz. Spray Bottle	02486	0 47719 2486 6	6 00 47719 02486 8	18.25" x 9.63" x 12"	12	29 lb.	2,109	40 cs	42" x 42"
1 Gal. Jug w/Sprayer	02481	0 47719 2481 1	4 00 47719 02481 9	15.5" x 9" x 12"	4	34 lb.	327	36 cs.	42" x 42"

Keep out of reach of children

Read and carefully follow all information on this Technical Data Bulletin, on the product label and the material safety data sheet for this product. To the best of our knowledge, the data contained herein are true and accurate at the date of issuance and are subject to change without prior notice. User must contact Rust-Oleum to verify correctness before specifying or ordering. No guarantee of accuracy is given or implied. We guarantee our products to conform to Rust-Oleum's quality control and assume no responsibility for coverage, performance or injuries from use. Visit Zinsser.com for our most up-to-date technical data bulletins.

Rust-Oleum Corporation, 11 Hawthorn Parkway, Vernon Hills, IL 60061

An RPM Company

Phone: 847•367•7700

www.rustoleum.com