RUST-OLEUM®
11 Hawthorn Parkway
Vernon Hills, IL 60061
An RPM Company

Technical Data Bulletin

MAGIC STRIP® CITRUS-ACTION

WORKS ON WOOD, METAL, FIBERGLASS & MORE

Product No.
42102
42104

Removes: Paint, Lacquer, Shellac, Varnish, Polyurethane & Other Finishes

Performance Characteristics:

- **DEEP-PENETRATING** – Stays active for up to 24 hours, Removes multiple layers in 1 easy step
- **SAFE FOR INDOOR USE** – Low-odor, methylene chloride-free
- **BIODEGRADABLE FORMULA**

Recommended Uses:
This unique **Citrus-Action Gel** paint and varnish remover stays wet and active for up to 24 hours, stripping multiple layers in one easy step. It's orange scented, no harsh fume formula is methylene chloride-free and safe for indoor use. Use **MAGIC STRIP® CITRUS-ACTION GEL** to remove latex and oil-based paint, varnish, lacquer, enamel, polyurethane, shellac, acrylics, and epoxy from wood, metal, masonry, and fiberglass surfaces.

Application Data

Preparation – Spread newspapers or a dropcloth around work area in case of drips or spills. Mask any area not being stripped with plastic and masking tape. Protect eyes and skin, wear safety goggles and chemical resistant gloves. For best results, use in temperatures between 65˚F. to 85˚F.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-Approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Application Requirements

1. Shake well. Pour into metal container and apply a heavy coat with a natural bristle brush.
2. After 30 minutes (or up to 24 hours), scrape a small test area to see if finish is ready for removal. Removal time depends on the number of layers and type of coating being removed.
3. Gently scrape off old finish with a plastic stripping tool, putty knife or scrapper. When removing finish from wood, scrape in direction of wood grain. For stubborn areas, use an abrasive stripping pad dipped in **MAGIC STRIP® CITRUS-ACTION GEL**. Use a stripping brush to remove finish in recessed areas.
4. Wash surface with **ZINSSER STRIPPER WASH** before refinishing.

Cleanup – Tools and brushes should be cleaned with soap and water immediately after use.

First Aid – In case of eye contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately. In case of skin contact, wash thoroughly with soap and water for at least 15 minutes. Remove contaminated clothing and shoes. Get medical attention immediately. If you experience difficulty breathing leave the area to obtain fresh air, if continued difficulty is experienced get medical attention immediately. If swallowed contact a physician or poison control center immediately. Do not induce vomiting unless directed to do so by medical personnel.

Spillage – Open containers carefully and close after each use. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Clean up rags, papers and waste promptly. Allow solvent to evaporate then dispose of in a metal container.

Disposal – Call your local sanitation department for aid in disposing of unwanted product in your area or call the Environmental Protection Agency Solvent and Hazardous Waste hotline at 1-800-424-9345. Do not dump on the ground or in local sewer discharge system.

WARNING! – Contains N-Methyl Pyrrolidone, Dibasic Ester, and monoethanolamine. Keep away from heat and flame. Do not get in eyes, on skin or clothing. Do not breathe vapors or spray mist. Prevent build-up of vapors by opening windows and doors to achieve cross ventilation. **USE ONLY WITH ADEQUATE VENTILATION.** Vapor is harmful, it may affect the brain or nervous system causing dizziness, headache or nausea. NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. May cause nose and throat irritation. May be harmful if absorbed through skin. WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects, or other reproductive harm. Close container after each use. Wash thoroughly after handling. Wash clothing before re-use. Thoroughly clean contaminated shoes. **KEEP OUT OF REACH OF CHILDREN.**

Specification Data

Temperature Application Range	40˚F. – 90˚F.
Shelf Life	60 months @ 75˚F.
VOC	**49%**
Flash Point	> 200˚F.
Storage Condition	40˚F. – 90˚F.
Freeze/Thaw Stable	Yes

Packaging

Unit Size	Unit Code	Case Pack	Case Weight	Pallet Pack
1/2 gallon	42102	4	20 lbs.	60 cases
1 quart	42104	6	27 lbs.	84 cases

Warranty:
This product will perform as claimed if applied according to our directions. The directions apply to most applications, but may not cover special conditions, applications, techniques and/or surfaces. If you have a question, check with your dealer or contact Rust, Somerset NJ. Warranty is limited to replacement or refunded value of product actually used if such product proves to be defective within two years of manufacture.

Technical Assistance - Available through local authorized Rust-Oleum dealers. For the dealer nearest you call 847-367-7700 or visit our website at www.zinsser.com.

* Safer than methylene chloride based strippers.

Keep out of reach of children

Read and carefully follow all information on this Technical Data Bulletin, on the product label and the material safety data sheet for this product. To the best of our knowledge, the data contained herein are true and accurate at the date of issuance and are subject to change without prior notice. User must contact Rust-Oleum to verify correctness before specifying or ordering. No guarantee of accuracy is given or implied. We guarantee our products to conform to Rust-Oleum's quality control and assume no responsibility for coverage, performance or injuries from use. Visit Zinsser.com for our most up-to-date technical data bulletins.

Rust-Oleum Corporation, 11 Hawthorn Parkway, Vernon Hills, IL 60061
An RPM Company
Phone: 847•367•7700
www.rustoleum.com