

# **Technical Data Bulletin**

## READY-MIXED STUCCO PATCH

## (Formerly BONDEX)

Item# 60590, 60584

Zinsser Stucco Patch is a ready to use formula for the repair of cracks, chips, and breaks in stucco, concrete or masonry surfaces.

## **Properties:**

Weight:	Item #	<u>Size</u>	<u>Case</u>	<u>Case</u>	Cubic Ft.
			<u>Pack</u>	<u>Weight</u>	<u>Per Case</u>
	60584	1qt. 1 gal	6	22 lbs.	.38
	60590	1 gal	4	62 lbs.	1.04

Consistency: Paste

Coverage: Dependent upon depth and width of crack, hole or imperfection.

Tinting: N/A
Drying Time: 4-5 hours

Storage: Keep from freezing. Close container tightly

#### **DIRECTIONS:**

<u>Surface Preparation:</u> Area to be patched must be clean and free of any loose particles, powdery material and scaling paint. Prepare surface by scrubbing vigorously with a wire brush.

**Note:** For extra adhesion, the area to be patched should be primed with a bonding primer.

**Application:** Apply with a putty knife, broad knife, trowel or other suitable tool, working material well into distressed areas, filling and feathering edges. Deep fills greater than 1/2" require more than one application.

**<u>Finishing:</u>** If matching an existing stucco finish, allow the patch to "set" one-half hour and gently test the area with the finishing tool such as a stipple brush, sponge or trowel. The patch surface may be moistened with a few drops of water to aid finishing. The patch, if desired, may be primed and painted with a quality masonry paint. If material settles in container, mix thoroughly before use. If material is too stiff, add 1 teaspoon of clean water and stir thoroughly.

#### **CLEAN-UP:**

Clean tools with warm water immediately after use.

### **CAUTIONS:**

For exterior or interior use, apply only when temperature is above 50°F (10°C). Keep out of reach of children. Do not take internally. If Ready-Mixed Stucco Patch is swallowed, drink plenty of water and consult your physician. If it gets into eyes or on skin, flush with water.

### Keep out of reach of children

Read and carefully follow all information on this Technical Data Bulletin, on the product label and the material safety data sheet for this product. To the best of our knowledge, the data contained herein are true and accurate at the date of issuance and are subject to change without prior notice. User must contact Rust-Oleum to verify correctness before specifying or ordering. No guarantee of accuracy is given or implied. We guarantee our products to conform to Rust-Oleum's quality control and assume no responsibility for coverage, performance or injuries from use. Visit Zinsser.com for our most up-to-date technical data bulletins.

Rust-Oleum Corporation, 11 Hawthorn Parkway, Vernon Hills, IL 60061

An RPM Company
Phone: 847•367•7700

www.rustoleum.com