

ROLL-A-TEX ADDITIVES FOR PAINT

(Formerly Bondex)

Item# 22232, 22233, 22234

Roll-A-Tex is developed from a high-performance formula of additives and texturing materials, that when added to any paint, emulsifies and actually becomes part of the paint. Roll-A-Tex produces an extremely durable and even-flowing texture, with superior covering and “fill-in” qualities. The high quality properties of Roll-A-Tex make a professional-looking texture easy to achieve. Just mix with any paint and apply. Roll-A-Tex permanently fills and covers cracks and flaws. Eliminates the need for tedious and time-consuming crack repair. Hides building defects. Covers repaired surface in one coat, without priming. Prevents soaking, blotching and uneven paint coloring. Restores and beautifies in one low cost application with a roller or brush.

Apply Roll-A-Tex to any surface, old or new. It can be used on stucco, plaster, brick, drywall, concrete, cinder block, wood and roofs. Roll-A-Tex is available in three different formulas: Fine, Medium, and Coarse. Use the formula best suited for your application.



Fine Texture

For use on **interior** or **exterior** surfaces. With new construction, it's a “one-step” texture for any surface. For remodeling, it adds beauty and flair when repainting walls. This easy-to-apply texture covers hairline cracks and repaired surfaces.

Medium Texture

Used for **interior** or **exterior** applications, it provides excellent repair qualities to fill and cover moderately flawed and cracked surfaces. It may be used on smooth surfaces, where a strong textured look is desired, or with extensively cracked walls that require extra cover-up. It may be used to match most original exterior stucco textures, and has very good “fill-in” capabilities. Ideal for deteriorated surfaces in need of repainting.

Coarse Texture

Excellent for **interior** or **exterior** use, where superior “fill-in” and covering qualities are required. Ideal for use on large cracks and extensively repaired surfaces, or it may simply be used wherever a more defined texture appearance is desired. It provides attractive texturing to cinder block and brick in only one coat.

DIRECTIONS:

SURFACE PREPARATION:

Follow surface preparation direction on paint label.

MIXING:

While mixing we suggest you wear a NIOSH approved dust mask. In a separate container, add contents of package to one gallon of paint. Add less for good surfaces, and more for extremely bad surfaces. The more Roll-A-Tex you add, the greater the hiding and texturing qualities. Stir thoroughly and thin sparingly. For best results, keep mixture as thick as possible, yet still rollable. Avoid excessive roll-out by using a roller pan or grid.

APPLICATION:

Apply with light pressure and minimum roll-out on the surface; the less rolling, the better the texture. A second coat of Roll-A-Tex may be cross-rolled after partial or complete drying for a greater hiding and texturing effect.

CLEAN UP:

Clean tools with warm soap and water.

CAUTIONS:

Keep out of reach of children. Do not take internally. If ingested, drink plenty of water and get medical attention. In case of eye contact, flush with water for 15 minutes and get medical attention. On skin, wash with soap and water.

PROPERTIES:

<i>Color:</i>	<i>White</i>			
Weight:				
Item #	Size	Case Pack	Case Weight	Cubic Ft. Per Case
22232	1 lb.	6	7 lbs.	.43
22233	1 lb.	6	7 lbs.	.43
22234	1 lb.	6	7 lbs.	.43

Coverage: If applying with a roller use a 3/8" to 3/4" nap roller cover. Roll-A-Tex Fine will cover approximately 150-200 square feet depending upon the product application. Roll-A-Tex Medium will cover approximately 100-125 square feet. Roll-A-Tex Coarse will cover approximately 80-120 square feet.

Consistency: Powder

Drying Time: See paint drying time.

Toxicity: N/A

Flammability: N/A

Hazardous: N/A

Ingredients:

Keep out of reach of children

Read and carefully follow all information on this Technical Data Bulletin, on the product label and the material safety data sheet for this product. To the best of our knowledge, the data contained herein are true and accurate at the date of issuance and are subject to change without prior notice. User must contact Rust-Oleum to verify correctness before specifying or ordering. No guarantee of accuracy is given or implied. We guarantee our products to conform to Rust-Oleum's quality control and assume no responsibility for coverage, performance or injuries from use. Visit Zinsser.com for our most up-to-date technical data bulletins.

Rust-Oleum Corporation, 11 Hawthorn Parkway, Vernon Hills, IL 60061

An RPM Company

Phone: 847•367•7700

www.rustoleum.com