

**Spray-On™ Activator
for Pre-Pasted Borders &
Wallpaper**

SureGrip® Spray-On Activator for Pre-Pasted Borders & Wallpaper is a convenient, ready-to-use, effective way to activate the paste on all pre-pasted borders and wallpaper over painted or primed surfaces. It properly conditions the paper without over-wetting, which can remove the paste from the paper and cause tearing. Non-staining, easy water cleanup!

SureGrip® Spray-On Activator for Pre-Pasted Borders & Wallpaper eliminates the need for a water tray and takes over-saturation out of the equation, which improves bonding strength.

- **For hanging pre-pasted borders and wallpaper over painted or primed surfaces**
- **Activates paste on pre-pasted paper**
- **Convenient no-mess spray**
- **Eliminates need for water tray**

Selection Data

Generic Type – Synthetic polymer-based activator for pre-pasted borders and wallpaper.

Recommended Uses - Use for hanging all types of pre-pasted borders and wallpaper over painted or primed surfaces. Refer to the "ZINSSER SureGrip Adhesive Selection Chart" online at www.zinsser.com for detailed recommendations.

Not Recommended For - This product is not recommended for unpasted wallcoverings. It is not intended for hanging pre-pasted borders or wallpaper over bare drywall without the use of a primer, or for hanging over existing vinyl wallcovering or extremely rough surfaces such as concrete blocks or stucco. See "**Existing Vinyl Wallcovering or Rough Surfaces**" on page 2 for recommendations.

Application Data

Surface Preparation - Surface must be clean, dry, smooth and sound – free of dust, grease, wax, oil, old wallcovering adhesive, mold and mildew and other residue. Inspect surface for paint bonding, loose wallcoverings, damaged wallboard or plaster. Remove old or loose wallcovering and residual wallcovering adhesive with **DIF® Wallpaper Stripper**. Repair unsound surfaces. Seal loose paint or damaged drywall and skim coats with **GARDZ® High Performance Sealer** as needed.

If hanging over bare drywall or builder's flat, prime surface with an acrylic primer - either **SHIELDZ® Universal**, **SHIELDZ Universal PLUS**, or **SHIELDZ Clear Acrylic Wall Size**. Before proceeding with any unusual conditions, consult your wallcovering or adhesive supplier.

Application - Use only when temperature is above 50°F. Product is READY TO USE. DO NOT DILUTE. Lay wallpaper or border on a flat surface with the pasted side facing up. Hold spray nozzle 10-12 inches from the paper and spray generously over entire surface, making sure edges are covered. Avoid contact with the surface of embossed or delicate wallcovering. Book and hang border or wallcovering according to manufacturer's instructions.

Mold & Mildew - Eliminate pre-existing mold and mildew by washing the affected area with a solution of 3/4 cup of Clorox® Ultra Bleach to 1 gallon of clean water. Wear protection to prevent skin and eye contact. Quickly wash off any solution that comes in contact with your skin. Do not add ammonia or other cleaning products to the bleach solution. Rinse surface with clean water. Allow surface to dry thoroughly before applying wallcovering.

Bare or Painted Drywall - Wipe down drywall with a damp cloth to remove residual joint compound dust prior to priming.

Plaster - New plaster must age at least 90 days before hanging wallcovering. Prime prior to installation.

Glossy Surfaces - Glossy paint, paneling, metal, glass, plastic, etc. should be primed with either **SHIELDZ Universal**, **SHIELDZ Universal PLUS**, or **SHIELDZ Clear Acrylic Wall Size** prior to wallcovering installation. Metal surfaces should be primed with rust inhibiting **Bulls Eye 1-2-3® Primer**.

Existing Vinyl Wallcovering or Rough Surfaces - This product is not intended for hanging pre-pasted wallpaper or borders over existing wallcovering or extremely rough surfaces. For existing wallcovering, use either **SureGrip127 Vinyl Over Vinyl Wallcovering Adhesive**, **SureGrip® Universal Adhesive**, **SureGrip Border Adhesive For Wallpapered Surfaces** or **PREPZ® Pre-Pasted Wallpaper and Border Prep & Adhesive**.

For hanging over rough surfaces such as concrete blocks or stucco, use **SureGrip 127 Vinyl Over Vinyl Wallcovering Adhesive** according to label instructions.

Textiles and Delicate Wallcoverings - Take special care to keep the adhesive off the face of wallcovering. Some wallcovering can be stained by water alone. Test for stain resistance prior to the installation and hang according to manufacturer's instructions.

Coverage – 32 ounces will hang up to 8 to 10 rolls of 6" border or 55 sq. ft. Spread rate may differ with various backings.

Dry Time - Drying time will vary depending on the wallcovering type, temperature, ventilation and humidity of the room.

Cleanup - Remove excess adhesive on or around the wallcovering immediately with clean water. Additional effort may be required if adhesive is allowed to contact the surface of embossed or textured vinyl. Close container tightly after each use.

Tool Cleanup - Clean tools with warm water.

Storage/Shelf Life/Disposal - Protect from freezing. Always keep the container tightly closed and store in a cool dry place at temperature between 40°F to 100°F. Normal storage life is five years. The disposal of excess or left over product should conform to local laws regarding water-based products.

Caution - Avoid contact with eyes. In case of eye contact, flush eyes with plenty of water for at least 15 minutes. Do not take internally. If swallowed contact a physician or Poison Control Center. Use with adequate ventilation. Wash thoroughly after handling. **Keep Out of Reach of Children.**

Limited Warranty - This product will perform as claimed if applied according to our directions. The directions apply to most applications, but may not cover special conditions, applications, techniques and/or surfaces. If you have a question, check with your dealer or contact Rust-Oleum Corporation, Vernon Hills, IL (847) 367-7700. Warranty is limited to replacement or refunded value of product actually used if such product proves defective within one year of manufacture.

PHYSICAL & PERFORMANCE DATA

Appearance Dry:	Clear
Odor:	None
Viscosity:	65 – 80 cps
Thinning:	Do not dilute
Coverage:	8-10 spools of 6" border or 55 sq. ft./32oz (May vary depending on porosity and application method)
Cleanup:	With water
Recommended Application Range:	50° F to 100° F
Recommended Storage Temperature:	40° F to 100° F
Freeze/Thaw Stable:	Yes
Flammability:	Non-flammable, water based
Shelf Life:	60 months
Removal:	Wet strip
VOCs:	0
Toxicity:	Safe

Packaging and Shipping Information

Size	Item No.	Product UPC	Carton Code	Case Dimensions	Case Pack	Case Wt Lbs.	Case Vol. In.	Pallet Pack	Pallet Size
32 ounce	02896	0 4771902896 3	60 04771902896 5	12" x 9" x 18"	12	29	1.13	40	42" x 44"

Keep out of reach of children

Read and carefully follow all information on this Technical Data Bulletin, on the product label and the material safety data sheet for this product. To the best of our knowledge, the data contained herein are true and accurate at the date of issuance and are subject to change without prior notice. User must contact Rust-Oleum to verify correctness before specifying or ordering. No guarantee of accuracy is given or implied. We guarantee our products to conform to Rust-Oleum's quality control and assume no responsibility for coverage, performance or injuries from use. Visit Zinsser.com for our most up-to-date technical data bulletins.

Rust-Oleum Corporation, 11 Hawthorn Parkway, Vernon Hills, IL 60061

An RPM Company

Phone: 847•367•7700

www.rustoleum.com