TECHNICAL DATA





DIF® GEL READY-TO-USE **WALLPAPER STRIPPER**

DESCRIPTION AND USES

Zinsser [®] DIF [®] Gel- Ready-To-Use Wallpaper Stripper is a non-toxic, no-drip, ready-to-use wallpaper stripper which clings to the wallpaper surface and stay wet longer. It will effectively remove 75 square feet of wallpaper per 32 ounce spray and 300 square feet per gallon.

PRODUCTS

SKU	Description
2466	32 Fluid Ounces
2431	1-Gallon

PRODUCT APPLICATION

SURFACE PREPARATION

Spread a solvent resistant drop cloth covered with newspapers around the work area in case of drips and spills. Protect carpeting, furniture and porous ceilings before application. Protect eyes and skin. Wear safety goggles and chemical resistant gloves.

PRODUCT APPLICATION (cont.)

Note: Ensure good cross ventilation during application. Wear a NIOSH approved respirator when spraying.

APPLICATION

Spray on or sponge apply DIF Gel Ready-To-Use on the wallpaper surface. Do not use a fine mist sprayer. Protect adjacent areas from overspray. Wait 15-20 minutes and scrape off with the Paper Scraper[™]. If the top layer does not peel off easily, score (10 holes per square inch) with Paper Tiger[™] and apply more DIF Gel Ready-To-Use Wallpaper Stripper. Allow DIF to penetrate for 10-15 additional minutes. Repeat the application if necessary. To remove residual adhesive, re-apply DIF Gel, wait 15-20 minutes and scrape or sponge off. Rinse with clean water. KEEP OUT OF REACH OF CHILDREN.

SPILLAGE

If spilled, contain spilled material and remove with an inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Clean up rags, papers and waste promptly.

CLEAN-UP

Clean up tools and equipment with soap and water.

Form: GDH-209 Rev.: 102813

TECHNICAL DATA



DIF® GEL READY-TO-USE WALLPAPER STRIPPER

PHYSICAL PROPERTIES

Physical Properties		GEL READY-TO-USE WALLPAPER STRIPPER
Composition		Acrylic Polymer, Disodium Ethylenediaminetetraacetate, Water
Weight	Per Gallon	8.3 lbs.
	Per Liter	1.00 kg
Volatile Organic Compounds		0 g/l
Practical Coverage		Varies with porosity of wallpaper
Shelf Life		5 years
Flash Point		200°F (93°C)
Caution!		Avoid contact with eyes and skin. If eye contact occurs, flush with water for at least 15 minutes. If irritation persists, seek medical attention. Do not take internally. KEEP OUT OF REACH OF CHILDREN.
Safety Information		For additional information, see MSDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Phone: 877•385•8155 www.rustoleum.com Form: GDH-209 Rev.: 102813