GARDZ®
SURFACE SEALER

DESCRIPTION AND USES

GardZ® Surface Sealer provides a clear, moisture-resistant foundation for porous surfaces before patching, priming, painting or wallpapering. Use GardZ to seal adhesive residue, patched drywall or plaster, textured walls, popcorn or acoustic ceilings.

PERFORMANCE CHARACTERISTICS

- Convenient spray-on formula
- Seals torn drywall
- Seals adhesive residue prior to painting or wallpapering
- Spot primes porous surfaces before and after patching

PRODUCTS

SKU	Description
249202	16-ounce Spray

PRODUCT APPLICATION

SURFACE PREPARATION

Surfaces must be clean, dry and sound. Remove all dirt, grease, oil, salt and chemical contaminants by washing the surface with a commercial detergent, or other suitable cleaning method. Rinse with fresh water and allow to thoroughly dry. Remove loose paint and material with a wire brush or sandpaper.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-Approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

PRODUCT APPLICATION (cont.)

APPLICATION

USE ONLY WITH ADEQUATE VENTILATION. Apply only when air and surface temperatures are between 65-90ºF (18-32ºC) and the relative humidity is below 85%. Apply GardZ liberally until the surface is covered. Properly sealed surfaces will have a slight and uniform sheen when viewed at an angle. Dries to the touch in 30 minutes. Allow 3 hours before patching, painting or wallpapering.

CLEAN-UP

Clean up splatters with soap and warm water before they dry. To prevent clogging after use, remove trigger and tube assembly, place in a container of clean water and rinse by spraying several times.

TECHNICAL DATA

GARDZ® SURFACE SEALER

PHYSICAL PROPERTIES

Physical Properties		SURFACE SEALER
Resin		Styrene Acrylic Latex
Weight	**Per Gallon**	8.5 lbs.
	Per Liter	1.02 kg
Volatile Organic Compounds		<30 g/l
Practical Coverage		Varies with type and porosity of surface
Shelf Life		5 years
Flash Point		200ºF (93C)
Caution!		Do not get in eyes. In case of eye contact, flush eyes with plenty of water for at least 15 minutes. Do not take internally. Avoid contact with skin and clothing. Wash thoroughly after handling. **KEEP OUT OF REACH OF CHILDREN.**
Safety Information		For additional information, see MSDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.

RUST-OLEUM BRANDS

Rust-Oleum Corporation
11 Hawthorn Parkway
Vernon Hills, Illinois 60061
An RPM Company

Phone: 877•385•8155
www.rustoleum.com

Form: GDH-183
Rev.: 110813