SUREGRIP® 127 VINYL OVER VINYL WALLCOVERING ADHESIVE

DESCRIPTION AND USES

Rust-Oleum® SureGrip® 127 Vinyl over Vinyl Wallcovering Adhesive is a commercial grade, ready-to-use, high bond adhesive formulated for hanging vinyl wallcoverings (up to 21 oz. commercial grade type I and II), foil and borders over existing vinyl wallcoverings or other non-porous or difficult surfaces such as paneling, textures, concrete, stucco, glass, metal, wood and plastic, without the need to prime. This product has excellent resistance to humidity. SureGrip 127 can also be used to secure overlapping wallcoverings at corners, windows or archway and is suitable for repairing curled edges and loose seams. SureGrip 127 is recommended for use with pasting machines.

SureGrip 127 is not recommended for use over wallcoverings that have high shrinkage tendencies such as grass cloth, string and other natural and textile materials. This product is not intended for use over silicone wax-coated surfaces or non-stick surfaces treated with Teflon®, Tedlar® and other similar non-stick coatings without prior surface preparation.

PERFORMANCE CHARACTERISTICS

- For installations over vinyl wallcovering, textured or other hard-to-stick surfaces
- No priming required
- Excellent wet tack, strong final bond
- Spreads and flows easily – Ideal for pasting machines
- Mold & mildew resistant adhesive

PRODUCTS

SKU	Container Size
02841	1-Gallon
02840	5-Gallon

PRODUCT APPLICATION

SURFACE PREPARATION

Surfaces must be clean, dry, sound and free of dust, grease, wax, oil, old wallcovering adhesive, mold and mildew and other residue. Inspect the surface for paint bonding, loose wallcoverings, damaged wallboard or plaster. Remove old or loose wallcovering and residual wallcovering adhesive with DIF® Wallpaper Stripper. Repair unsound surfaces. Seal loose paint or damaged drywall and cured skim coats with Gardz® High Performance Sealer as needed.

PRODUCT APPLICATION (cont.)

Mold & Mildew

Eliminate pre-existing mold and mildew by washing the affected area with a solution of ¾ cup of bleach to 1 gallon of water. Wear protection to prevent skin and eye contact. Quickly wash off any solution that comes in contact with your skin. Do not add ammonia or other cleaning agents to the bleach solution. Rinse surface with clean water. Allow surface to dry thoroughly before applying wallcovering.

Drywall

This product is non-strippable, therefore application over bare drywall is not recommended. If drywall protection is desired, install a removable heavy duty liner paper according to manufacturer's instructions before hanging wallcovering.

Plaster

New plaster must age at least 90 days before hanging wallcovering. Prime prior to installation with either ShieldZ Universal, ShieldZ Universal Plus, ShieldZ Clear Acrylic Wall Size or ShieldZ Oil-Base Wallcovering Primer.

Glossy Surfaces

No priming is required for glossy surfaces such as glossy paint, paneling, existing vinyl wallcovering, metal, glass and plastic. Metal surfaces should be primed with rust inhibiting Bulls- Eye® 1-2-3 Primer. Silicone, wax-coated surfaces or no-stick surfaces treated with Teflon®, Tedlar® and similar non-stick coatings should be thoroughly cleaned, sanded and primed prior to hanging.

Existing Vinyl Wallcovering or Rough Surfaces

Apply adhesive to the existing surface and allow to dry for at least one hour and then apply adhesive to new wallcovering and hang.

Borders and Wallpaper

When hanging paper-backed borders and wallpaper, dampen the back with a moist sponge and wait five minutes before applying SureGrip 127 Vinyl over Vinyl Wallcovering Adhesive.

PRODUCT APPLICATION (cont.)

APPLICATION

Use only when temperature is between 50-100°F (10-38°C) and the relative humidity is less than 85%. Adhesive is ready to use. DO NOT DILUTE. Apply a thin even coat using a roller, brush or pasting machine to the back of the wallcovering. Make sure sufficient adhesive is on edges. Avoid contact with the surface of embossed or delicate wallcovering. Book and hang wallcovering according to the manufacturer's instructions.

COVERAGE

One gallon of adhesive will hang up to 4 to 5 double rolls or 280 square feet. Spread rate may differ with various backings.

DRY TIME

Drying time will vary depending on the wallcovering type, temperature, ventilation and humidity in the room.

CLEAN-UP

Remove excess adhesive on or around the wallcovering immediately with clean water. Additional effort may be required if adhesive is allowed to contact the surface of embossed or textured vinyl. Close container tightly after each use.

TOOL CLEAN-UP

Clean tools with warm water.

STORAGE

Protect from freezing. Always keep the container tightly closed and store in a cool dry place at temperatures between 40-100°F (4-38°C).

TECHNICAL DATA

SUREGRIP® 127 VINYL OVER VINYL WALLCOVERING ADHESIVE

PHYSICAL PROPERTIES

	SureGrip 127 Vinyl Over Vinyl Wallcovering Adhesive
Resin Type	Modified Starch and Synthetic Polymer
Solvents	Water
Appearance	Clear
Odor	Mild
Solids by Weight	22.5-24.5%
Volatile Organic Compounds	<10 g/l (0.083 lbs./gal.)
Practical Coverage at Recommended DFT (assumes 15% material loss)	280 sq.ft./gal. Depending on porosity and application method
Dry Times at 70-80°F (21-27ºC) and 50% Relative Humidity	Drying time will vary depending on the wallcovering type, temperature, ventilation and humidity in the room.
Shelf Life	1 year
Flammability	Non-flammable
Flash Point	>200ºF (93ºC)
Safety	For additional information, see MSDS
NOTE:	Calculated values may vary slightly from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.

RUST-OLEUM BRANDS

Rust-Oleum Corporation
11 Hawthorn Parkway
Vernon Hills, Illinois 60061
An RPM Company

Phone: 877•385•8155
www.rustoleum.com

Form: GDH-133
Rev.: 080113