

SUREGRIP® HEAVY DUTY CLEAR PLUS COMMERCIAL WALLCOVERING ADHESIVE

DESCRIPTION AND USES

Zinsser® SureGrip® Heavy Duty Mold & Mildew-Proof Commercial Wallcovering Adhesive is a clear strippable wallcovering adhesive designed to prevent mold and mildew growth. SureGrip Plus eliminates problems such as staining, loose seams, and buckling wallcovering caused be mold and mildew. It is easy to spread and flows easily in a paste machine without the need to add water that can contaminate the adhesive.

PERFORMANCE CHARACTERISTICS

- · For use with vinyl and other commercial wall coverings
- Prevents mold & mildew growth, mildew stains, and musty odors
- Non-dilution formula prevents loose seams, curling edges and buckling wall covering
- Excellent wet tack and extended open time for trouble-free booking and double-cutting
- Spreads and flows easily Ideal for pasting machines
- · Non-staining, easy clean-up

Designed for use for preparing existing, remodeled or new construction surfaces for wallcovering installations, for use over previously painted or wallpapered surfaces, and on any surface where mold and mildew growth under the wallcovering is a concern and on any drywall surface where permeability is unknown. Use for hanging most types and weights of commercial wallcoverings from lightweight to heavyweight vinyl (woven fabric or paperbacked up to 40 oz. commercial grades types I, II, and III to delicate and special coverings such as silk, suede, grasscloth, string, fabric, and foil.

PRODUCTS

SKU Container Size
02830 5 GALLON

PRODUCT APPLICATION

SURFACE PREPARATION

Surfaces should be clean, dry, sound and free of dust, grease, wax, oil, old wallcovering adhesive, mold and mildew and other residue. Inspect the surface for paint bonding, loose wallcoverings, damaged wallboard or plaster. Remove old or loose wallcovering and residual wallcovering adhesive with DIF® Wallpaper Stripper. Repair unsound surfaces. Seal loose paint or damaged drywall and fully cured skim coats with Gardz® High Performance Sealer as needed.

PRODUCT APPLICATION (cont.)

Mold & Mildew

Eliminate pre-existing mold and mildew by washing the affected area with Perma-Wash™ Disinfectant and Fungicide Interior Concentrate according to the label directions. To remove stains, clean with Jomax® Mold & Mildew Stain Remover or a solution of ¾ cup of bleach to 1 gallon of water. Wear protection to prevent skin and eye contact. Quickly wash off any solution that comes in contact with your skin. Do not add ammonia or other cleaning agents to the bleach solution. Rinse surface with clean water. Allow surface to dry thoroughly before applying wallcovering.

Drywall

Wipe down with a damp cloth to remove residual joint compound dust prior to priming.

Plaster

New plaster must age at least 90 days before hanging wallcovering. Prime prior to installation.

Prime all surfaces including previously coated surfaces, paneling, glass, plastic, etc. with Shieldz[®] Universal PLUS Mold & Mildew-Proof Commercial Wallcovering Primer prior to wallcovering installation. Metal surfaces should be primed with rust inhibiting Bulls-Eye 1-2-3[®] Primer.

Existing Vinyl Wallcovering

This product is not intended for hanging wallcovering over existing vinyl wallcovering. For hanging directly over vinyl, use SureGrip® 127 Vinyl over Vinyl Wallcovering Adhesive according to label instructions. For hanging borders over vinyl, use SureGrip® Border Adhesive for Wallpapered Surfaces.

Textile/Delicate/Polyolefin/Polyester Backed Wallcoverings

Take special care to keep the adhesive off the face of textile or delicate wallcovering. Some wallcovering can be stained by water alone. Test for stain resistance prior to installation and hang according to manufacturer's instructions.

Wallcovering Removal

Wait 30 days or longer for primer and wallcovering adhesive to fully cure before removing vinyl wallcovering.

ENVIRONMENTAL CONDITIONS

The recommended temperature range for application is between 65-85°F (18-29°C) with less than 50% relative humidity where the HVAC has been environmentally controlled for at least 4 days before wallcovering installation and the temperature is maintained after the installation.

1 Form: CS2229 Rev.: 031213

TECHNICAL DATA



SUREGRIP® HEAVY DUTY CLEAR PLUS COMMERCIAL WALLCOVERING ADHESIVE

PRODUCT APPLICATION (cont.)

MIXING

Mix thoroughly with a drill motor to ensure any settled pigment is re-dispersed. DO NOT THIN.

APPLICATION

Apply an even coat using a roller, brush or pasting machine. Make sure sufficient adhesive is on edges. Avoid contact with the surface of embossed or delicate wallcovering. Double cut within 1 hour after hanging. More porous substrates may require quicker double cutting. Book and hang wallcovering according to the manufacturer's instructions.

Use a separate pail if applying adhesive by roller and store the balance of undiluted adhesive in the original pail with the original lid secured. Each pail of adhesive should be used within 24 hours after opening to minimize contamination.

Adhesive rollers, brushes and past machines must be cleaned daily to prevent contamination or spoilage. Seal partially used containers between uses and do not use paste that has been repeatedly opened and closed or stored longer than two days after opening.

After installing 3 sheets, inspect the wallcovering for proper installation and adhesive compatibility with wallcovering. If a problem occurs, stop and contact Rust-Oleum Corporation.

CLEAN-UP

Remove excess adhesive on or around the wallcovering immediately with clean water. Additional effort may be required if adhesive is allowed to contact the surface of embossed or textured vinyl. Close container tightly after each use.

Form: CS2229

2

Rev.: 031213

TECHNICAL DATA



SUREGRIP® HEAVY DUTY CLEAR PLUS COMMERCIAL WALLCOVERING ADHESIVE

PHYSICAL PROPERTIES

		SureGrip Plus Mold & Mildew-Proof Commercial Wallcovering Adhesive
Resin Type		Starch-based Adhesive
Solvents		Water
Appearance		Clear
Odor		Mild
Solids by Weight		32-34%
Volatile Organic Compounds		<10 g/l (0.083 lbs./gal.)
Practical Coverage at Recommended		280 sq.ft./gal. (6.9 m²/l)
DFT (assumes 15% material loss)		Depending on porosity and application method
Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity	Touch	1 hour
	Recoat	1 hour
Shelf Life		1 year
Flammability		Non-flammable
Flash Point		>200°F (93°C)
Safety		For additional information, see MSDS
NOTE:		Calculated values may vary slightly from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Phone: 877•385•8155 www.rustoleum.com Form: CS2229 Rev.: 031213