WOOD BLEACH

DESCRIPTION AND USES

Zinsser® Wood Bleach is designed to brighten all wood surfaces including trim, paneling, floors and furniture. It bleaches new or stripped wood to a lighter, more uniform color.

PRODUCTS

SKU	Description
42138	Two 8 ounce bottles

PRODUCT APPLICATION

IMPORTANT

This product is for indoor use only. Test on inconspicuous area before applying to ensure favorable results. Wear old clothes and shoes, eye protection and rubber gloves during use.

SURFACE PREPARATION

Remove all dirt, oil, grease, and surface contamination by washings with soap and water or a suitable commercial detergent. Rinse with fresh water and allow to dry thoroughly. Remove loosely adhered previous coatings by scraping and sanding. Remove all sanding dust and dirt with a vacuum and grease or glue with a clean rag dampened with mineral spirits.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

PRODUCT APPLICATION (cont.)

DIRECTIONS FOR USE

Spread a solvent resistant drop cloth around the work area in case of drips or spills. Protect eyes and skin. Wear safety goggles and chemical resistant gloves. Amount of bleaching will vary with the type of wood and length of treatment time.

Apply Solution A with a new sponge, completely saturating the area to be bleached. Let stand 5 minutes for soft woods and 10 minutes for hard woods. While surface is still wet, use another sponge to apply Solution B over Solution A. Let stand overnight to dry.

Sand lightly to remove residue and lighten wood. If a lighter shade is desired, repeat the process.

CAUTION! Avoid contact with eyes and skin. If eye contact occurs, flush with water for at least 15 minutes. If irritation persists, seek medical attention. Avoid contact with the skin. Wash exposed areas with soap and water. Do not take internally. **KEEP OUT OF REACH OF CHILDREN.**

TECHNICAL DATA

WOOD BLEACH

PHYSICAL PROPERTIES

	WOOD BLEACH
Composition	Sodium Hydroxide, Hydrogen Peroxide
Weight per Gallon	9.1 lbs.
Per Liter	1.1 kg
pH	N/D
VOC (Based on Consumer Product Rule)	<0.1%
Shelf Life	3 years
Practical Coverage	Varies with wood type
Flash Point	>200ºF (93ºC)
Caution!	Contains sodium hydroxide. May cause eye irritation. Flush eyes immediately with large amounts of water for at least 15 minutes. Get medical attention. Avoid contact with skin. Wash exposed areas thoroughly with soap and water. Get medical attention. Do not swallow. If swallowed, contact a physician, poison control center, or hospital emergency room. **DO NOT INDUCE VOMITING.** Use only with adequate ventilation. **KEEP OUT OF REACH OF CHILDREN**.
Safety Information	For additional information, see MSDS.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.

RUST-OLEUM BRANDS

Rust-Oleum Corporation
11 Hawthorn Parkway
Vernon Hills, Illinois 60061
An RPM Company

Phone: 877•385•8155
www.rustoleum.com

Form: GDH-15
Rev.: 032213