ZINSSER®
DETAIL STRIPPER

DESCRIPTION AND USES

Zinsser ® Detail Stripper is a deep penetrating formula designed for intricate and detailed removal projects. Easily flows into carvings, grooves, scrolls and small and hard-to-reach areas. Detail Stripper works on fine wood, fine furniture and antiques to remove latex and oil-based paints, stains, clear finishes, wax, lacquer, shellac, varnish and polyurethane in 20-30 minutes. Will not harm wood or raise grain.

PERFORMANCE CHARACTERISTICS

- Deep penetrating for fine wood and detailed removal projects.
- Works in 20-30 minutes
- Excellent for furniture and antiques
- Will not harm wood or raise grain

PRODUCTS

SKU	Description
42121	1-Gallon
42127	1-Quart

PRODUCT APPLICATION

SURFACE PREPARATION

Spread a solvent resistant drop cloth covered with newspapers around the work area in case of drips and spills. Protect eyes and skin. Wear safety goggles and chemical resistant gloves. Keep away from heat, sparks and flames.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-Approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

PRODUCT APPLICATION (cont.)

APPLICATION

USE ONLY WITH ADEQUATE VENTILATION. Apply only when air and surface temperatures are between 65-90ºF (18-32ºC) and the relative humidity is below 85%. Shake can before using and open can carefully to relieve pressure. Pour Zinsser Detail Stripper into a glass or metal container. Use an inexpensive natural bristle brush to apply. Brush on a small section at a time. Apply in one direction. Allow 20-30 minutes for the stripper to work. Test a small area to see if the finish is ready for removal by using a plastic scraping tool. As long as the stripper is wet, it is working.

Remove the softened finish by gently scraping in the direction of the wood grain with a plastic scraping tool or steel wool. Multiple coats of finishes may require repeat application. Use a stripper brush, scrub brush or pointed stylus to remove old finish in deep recesses. Wipe entire surface in the direction of the grain with a clean piece of steel wool dipped in Detail stripper. To further remove stain from wood, use either Zinsser Power Stripper or Zinsser Wood Bleach. Wash the surface with Zinsser Stripper Wash before refinishing.

SPILLAGE

Open containers carefully and close after each use. If spilled, contain spilled material and remove with an inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Clean up rags, papers and waste promptly. Allow solvent to evaporate and then dispose of in a metal container.

CLEAN-UP

Clean up tools and brushes with soap and water.

TECHNICAL DATA

ZINSSER® DETAIL STRIPPER

PHYSICAL PROPERTIES

Physical Properties		DETAIL STRIPPER
Composition		Acetone, Methanol, Methylene Chloride, Toluene
Weight	**Per Gallon**	7.4 lbs.
	Per Liter	0.90 kg
Volatile Organic Compounds		650 g/l
Practical Coverage		Varies with thickness and type of coating
Shelf Life		5 years
Flash Point		-4ºF (-20ºC)
Caution!		Cannot be made non-poisonous. Do not get in eyes, on skin or clothing. Causes eye and skin burns, nose and throat irritation. May be harmful if absorbed through skin. Wash thoroughly after handling. **KEEP OUT OF REACH OF CHILDREN.**
Safety Information		For additional information, see MSDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.

RUST-OLEUM BRANDS

Rust-Oleum Corporation
11 Hawthorn Parkway
Vernon Hills, Illinois 60061
An RPM Company

Phone: 877•385•8155
www.rustoleum.com

Form: GDH-181
Rev.: 092013