ZINSSER®
BRUSH & ROLLER WASH

DESCRIPTION AND USES

Zinsser ® Brush & Roller Wash effectively cleans and restores all brushes, paint rollers and spray equipment. It works on shellac, lacquer, varnish, oil-based and latex pants, polyurethane and other synthetic finishes. It is suitable for use on synthetic and natural bristle brushes and contains no acid or alkali.

PERFORMANCE CHARACTERISTICS

- Dissolves all types of paints and finishes
- Cleans brushes and rollers in minutes
- Easy water clean up

PRODUCTS

SKU	Description
42094	1-Quart

PRODUCT APPLICATION

SURFACE PREPARATION

Spread a solvent resistant drop cloth covered with newspapers around the work area in case of drips and spills. Protect eyes and skin. Wear safety goggles and chemical resistant gloves. Keep away from heat, sparks and flames.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-Approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

PRODUCT APPLICATION (cont.)

APPLICATION

USE ONLY WITH ADEQUATE VENTILATION. Apply only when air and surface temperatures are between 65-90ºF (18-32ºC) and the relative humidity is below 85%. Immediately after painting, pour ¾ of Brush& Roller Wash contents into a container large enough to cover equipment to be cleaned, reserving the remaining ¼ for the final wash. Place brushes, rollers or spray guns into the container and cover to retard evaporation. Allow equipment to soak for 10-15 minutes. The time required may vary depending on the age, thickness and type of coating that is being removed. Rinse tools and equipment in fresh Brush & Roller Wash and follow up with clean water. Shake brushes and dry with a clean cloth. Always hang brushes to dry.

FOR HARDENED BRUSHES AND ROLLERS – Allow hardened brushes and rollers to soak 2-6 hours, overnight or until the dried paint is softened. Separate brush bristles with a wire brush, then work brush against the bottom of the wash filled container to promote paint softening. For rollers, work nap with a scraping tool to loosen paint and re-soak in Brush & Roller Wash. Rinse brushes and rollers in fresh Brush & Roller Wash followed by rinsing with clean water.

FOR SPRAY EQUIPMENT – Spray Brush & Roller Wash through the equipment. Disassemble the equipment and soak parts until the paint is softened and loosened. Rinse with fresh Brush & Roller Wash followed by rinsing with clean water.

SPILLAGE

Open containers carefully and close after each use. If spilled, contain spilled material and remove with an inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Clean up rags, papers and waste promptly. Allow solvent to evaporate, then dispose of in a metal container.

CLEAN-UP

Clean up tools and brushes with soap and water.

TECHNICAL DATA

ZINSSER® BRUSH & ROLLER WASH

PHYSICAL PROPERTIES

Physical Properties		BRUSH & ROLLER WASH
Composition		Methanol, Methylene Chloride, Methyl Ethyl Ketone, Toluene
Weight	**Per Gallon**	7.6 lbs.
	Per Liter	0.91 kg
Volatile Organic Compounds		696 g/l
Practical Coverage		Varies with thickness and type of coating
Shelf Life		5 years
Flash Point		25ºF (-4ºC)
Caution!		Cannot be made non-poisonous. Causes eye, skin, nose and throat irritation. Do not get in eyes, on skin or clothing. May be harmful if absorbed through skin. Wash thoroughly after handling. **KEEP OUT OF REACH OF CHILDREN.**
Safety Information		For additional information, see MSDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.

RUST-OLEUM BRANDS

Rust-Oleum Corporation
11 Hawthorn Parkway
Vernon Hills, Illinois 60061
An RPM Company

Phone: 877•385•8155
www.rustoleum.com

Form: GDH-185
Rev.: 092013