MAGIC STRIP®
CITRUS-ACTION GEL

DESCRIPTION AND USES

Magic Strip® Citrus-Action Gel is a paint and varnish remover designed to stay wet and active for up to 24 hours, stripping multiple layers of paint in one easy step. It is citrus scented with no strong fumes and is methylene chloride free and safe for indoor use. It is suitable for removing latex and oil-based paint, varnish, lacquer, polyurethane, shellac, acrylics and epoxy from wood, metal, masonry and fiberglass surfaces.

PERFORMANCE CHARACTERISTICS

- Deep penetrating – stays active for up to 24 hours
- Removes multiple layers in one easy step
- Safe for indoor use
- Low odor, pleasant scent
- Biodegradable formula
- Excellent for wood, metal and masonry

PRODUCTS

SKU	Description
42102	½-Gallon
42104	1-Quart

PRODUCT APPLICATION

SURFACE PREPARATION

Spread a solvent resistant drop cloth covered with newspapers around the work area in case of drips and spills. Protect eyes and skin. Wear safety goggles and chemical resistant gloves. Keep away from heat, sparks and flames.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-Approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

PRODUCT APPLICATION (cont.)

APPLICATION

USE ONLY WITH ADEQUATE VENTILATION. Apply only when air and surface temperatures are between 65-85ºF (18-29ºC) and the relative humidity is below 85%. Shake well before using. Pour Magic Strip into a metal container and apply a heavy coat with a natural bristle paint brush. Apply in one direction. After 30 minutes (or up to 24 hours) scrape a small area to see if the finish is ready for removal. Removal; time depends on the number of layers and type of coating being removed.

Gently scrape off all old finish with a plastic stripping tool, putty knife or scraper. When removing finish from wood, scrape in the direction of the wood grain. For stubborn areas, use an abrasive stripping pad dipped into Magic Strip Citrus-Action Gel. Use a stripping brush to remove finish in recessed areas. Wash surface with Zinsser Stripper Wash before refinishing.

SPILLAGE

Open containers carefully and close after each use. If spilled, contain spilled material and remove with an inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Clean up rags, papers and waste promptly. Allow solvent to evaporate and then dispose of in a metal container.

CLEAN-UP

Clean up tools and brushes with soap and water.

TECHNICAL DATA

MAGIC STRIP® CITRUS-ACTION GEL

PHYSICAL PROPERTIES

Physical Properties		MAGIC STRIP CITRUS-ACTION GEL
Composition		n-Methyl 2-Pyrrolidone, Dibasic Ester, Monoethanolamine
Weight	**Per Gallon**	8.8 lbs.
	Per Liter	1.05 kg
Volatile Organic Compounds		516 g/l
Practical Coverage		Varies with thickness and type of coating
Shelf Life		5 years
Flash Point		200ºF (93ºC)
Caution!		Do not get in eyes, on skin or clothing. DO NOT breathe vapors or spray mist. Causes skin, nose and throat irritation. May be harmful if absorbed through skin. Wash thoroughly after handling. **KEEP OUT OF REACH OF CHILDREN.**
Safety Information		For additional information, see MSDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.

RUST-OLEUM BRANDS

Rust-Oleum Corporation
11 Hawthorn Parkway
Vernon Hills, Illinois 60061
An RPM Company

Phone: 877•385•8155
www.rustoleum.com

Form: GDH-177
Rev.: 102113