MAGIC STRIP®
PAINT & VARNISH REMOVER

DESCRIPTION AND USES

Magic Strip® Paint & Varnish Remover is a low odor, non-flammable paint & varnish remover that strips up to 7 layers of most oil and water-based paints and varnishes in one application. It is suitable for use on interior and exterior surfaces including wood, brick, stone, masonry, metal and fiberglass. Magic Strip goes on green and changes to a pale green to indicate when it is time to strip the surface.

PERFORMANCE CHARACTERISTICS

- Removes up to 7 layers in one application
- Biodegradable and non-flammable
- Changes color when time to strip

PRODUCTS

SKU	Description
42072	½-Gallon
42074	1-Quart

PRODUCT APPLICATION

SURFACE PREPARATION

Mask any area not being stripped with plastic and masking tape. Spread a solvent resistant drop cloth covered with newspapers around the work area in case of drips and spills. Protect eyes and skin. Wear safety goggles and chemical resistant gloves. Keep away from heat, sparks and flames.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-Approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

PRODUCT APPLICATION (cont.)

APPLICATION

USE ONLY WITH ADEQUATE VENTILATION. Apply only when air and surface temperatures are between 60-80ºF (16-27ºC) and the relative humidity is below 85%. Shake well before using. With an inexpensive brush, apply a heavy coat of Magic Strip over the entire surface to be stripped. Allow Magic Strip to work. Color change to pale green generally occurs within 4-24 hours. The time required will depend on the thickness and type of coating being removed.

Use a putty knife or scraper to gently lift paint from the surface. Magic Strip will often form a skin to allow it to work longer without drying out. To soften the skin and make paint removal easier, mist area with water. After removing paint, use a bristle brush or a stripping tool or pad dipped in Zinsser Stripper Wash for final clean-up of residue. Surface should be completely dry before refinishing.

SPILLAGE

Open containers carefully and close after each use. If spilled, contain spilled material and remove with an inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Clean up rags, papers and waste promptly. Allow solvent to evaporate and then dispose of in a metal container.

DISPOSAL

For disposal of rags and unused amounts of product, contact local or state government environmental control agency.

CLEAN-UP

Clean up tools and brushes with soap and water.

TECHNICAL DATA

MAGIC STRIP® PAINT & VARNISH REMOVER

PHYSICAL PROPERTIES

Physical Properties		MAGIC STRIP PAINT & VARNISH REMOVER
Resin		Vinyl Acrylic Latex
Pigment		Magnesium Silicate
Solvents		n-Methyl 2-Pyrrollidone, Water
Weight	**Per Gallon**	10.9 lbs.
	Per Liter	1.30 kg
Solids	**By Weight**	40.7%
	By Volume	25.5%
Volatile Organic Compounds		179 g/l
Practical Coverage		Varies with thickness and type of coating
Shelf Life		5 years
Flash Point		200ºF (93ºC)
Caution!		Do not get in eyes, on skin or clothing. DO NOT breathe vapors or spray mist. Causes skin, nose and throat irritation. May be harmful if absorbed through skin. Wash thoroughly after handling. **KEEP OUT OF REACH OF CHILDREN.**
Safety Information		For additional information, see MSDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.

RUST-OLEUM BRANDS

Rust-Oleum Corporation
11 Hawthorn Parkway
Vernon Hills, Illinois 60061
An RPM Company

Phone: 877•385•8155
www.rustoleum.com

Form: GDH-178
Rev.: 102113