RUST-OLEUM

FOOD GRADE SILICONE

DESCRIPTION AND USES

Rust-Oleum® Food Grade Silicone preserves, protects, lubricates and waterproofs. This product is effective in eliminating squeaks and noises caused by contact with dissimilar materials, and is non-staining.

This lubricant is certified by NSF to be category H1 compliant. This lubricant can be used with incidental food contact. It may be used as a lubricant or anti-rust film on equipment and machine parts in locations to edible products. It may also be used as a release agent on gaskets or seals of tank closures. The amount used should be the minimum required to accomplish the desired effect on the equipment. If used as an anti-rust film, the compound must be removed from the equipment surface by washing or wiping as required so not to contaminate food being processed.

For use on conveyors, O-rings, and tracks

For Professional Use Only.

FEATURES

- Repels water
- Can be used on painted surfaces, metal, wood, plastic, or rubber
- Can be used as a lubricate or protective coating

PRODUCTS

SKU	Container Size
273922	11 oz fill weight aerosol
274832	11 oz fill weight aerosol (Canada only)

PRODUCT APPLICATION

SURFACE PREPARATION

Surfaces must be dry and free of grease, oil, dirt, rust, wax, or other forms of surface contamination

APPLICATION

Use in a well ventilated area when temperatures are between 50 -90ºF (10-32ºC). Avoid spraying in very windy and dusty conditions.

Shake well before and during use. Hold can 10-16" from the surface and spray in a steady back-and-forth motion. When used as a lubricate, apply a heavy coat. When used as a protective coating, apply light coats and polish with a clean cloth. Repeat as necessary.

PRECAUTION

Vapors may ignite explosively. Keep away from heat, sparks and flame. Extinguish all flames and pilot lights, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Prevent buildup of vapors by opening all windows and doors to achieve cross ventilation. Avoid contact with eyes and skin.

CLEAN UP

Properly dispose of container and unused contents in accordance with local, state and federal regulations.

STORAGE

Store in cool dry areas and protect from excessive heat.

TECHNICAL DATA

FOOD GRADE SILICONE

PHYSICAL PROPERTIES

	Food Grade Silicone
Composition	Polysiloxane
Solvent	Hexane
Fill Weight	11 ounces
Shelf Life	5 years
Flash Point	-132ºF (-91ºC)
Safety information	For additional information, see MSDS.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.

RUST-OLEUM INDUSTRIAL BRANDS

Rust-Oleum Corporation
11 Hawthorn Parkway
Vernon Hills, Illinois 60061
An RPM Company

Phone: 877•385•8155
www.rustoleum.com/industrial

Form: GDH-49
Rev.: 081313