



PENETRANT

DESCRIPTION AND USES

Rust-Oleum® Penetrant permeates metal better than standard formulated penetrating oils. Under the most severe conditions, the foaming action provides constant lubrication while attacking the tough rusted areas.

For use on rusted bolts, threads, fittings, and other rusted surfaces.

For Professional Use Only.

FEATURES

- Heavy duty permeating action on tough rust
- Large 16 oz fill aerosol with 360° spray tip
- Leaves behind a protective film that resist moisture

PRODUCTS

SKU	Container Size
273920	16 oz fill weight aerosol
274826	16 oz fill weight aerosol (Canada only)

PRODUCT APPLICATION

APPLICATION

Use in a well ventilated area when temperatures are between 50 -90°F (10-32°C). Avoid spraying in very windy and dusty conditions.

Shake well before and during use. Hold can 10-16" from the surface and spray in a steady back-and-forth motion and allow a few minutes for penetration action before attempting to loosen heavily rusted or frozen parts. Repeat as necessary for areas with heavy deposits.

PRECAUTION

Vapors may ignite explosively. Keep away from heat, sparks and flame. Extinguish all flames and pilot lights, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Prevent buildup of vapors by opening all windows and doors to achieve cross ventilation. Avoid contact with eyes and skin.

CLEAN UP

Properly dispose of container and unused contents in accordance with local, state and federal regulations.

STORAGE

Store in cool dry areas and protect from excessive heat.

PHYSICAL PROPERTIES

	Penetrant
Composition	Aliphatic Hydrocarbons, Kerosene, Naphthenic Petroleum Oil
Fill Weight	16 ounces
Shelf Life	5 years
Flash Point	-141°F (-96°C)
Safety information	For additional information, see MSDS.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.