SATIN BLACK 7777

• TRUSTED QUALITY SINCE 1921 •

RUST-OLEUM®

STOPS RUST®

PROTECTIVE ENAMEL

SUPERIOR DURABILITY
PREMIUM QUALITY

DANGER!
COMBUSTIBLE LIQUID AND VAPOR.
HARMFUL OR FATAL IF SWALLOWED.
See other cautions on back panel.

OIL-BASED

8 FL. OZ. (1/2 PINT) 236mL

¡PELIGRO!
LIQUIDO Y VAPORES COMBUSTIBLES.
DAÑINO O FATAL SI INGIBE.
Observar otras precauciones al dorso.

Rust-Oleum® Stops Rust® Oil-Based Enamels provide excellent rust prevention when applied directly to metal. They also offer excellent coverage, chip resistance and color retention. For even longer lasting protection, use a Stops Rust Primer first.

Painting Conditions: Use when temperature is above 50°F (10°C) and humidity is below 85% to ensure proper drying. Do not apply to surfaces that exceed 200°F (93°C) or galvanized metal. **Preparation:** Remove loose paint and rust with a wire brush or sandpaper. Lightly sand glossy surfaces. Clean surface with soap and water, rinse and let dry. **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. **Painting:** Stir thoroughly. If thinning is necessary, thin material only with mineral spirits or acetone. For brush or roller, thin no more than 5%. Apply with a good quality brush, roller or spray gun. **Recoat Times:** May recoat when fully dry, usually in 24 hours. Dries to the touch in 2-4 hours and to handle in 5-9 hours, at 70°F (21°C) – 50% relative humidity. Allow more time at cooler temperatures and higher humidity. **Clean-up:** Clean brush, roller and other tools with mineral spirits.

CONTAINS PETROLEUM DISTILLATES. Vapor Harmful. May affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, skin, nose and throat irritation. **NOTICE:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Keep away from heat and flame. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. **Use only with adequate ventilation.** Do not breathe dust, vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for use. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. **KEEP OUT OF REACH OF CHILDREN. FIRST AID:** In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention immediately; for skin, wash thoroughly with soap and water. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. If swallowed, do not induce vomiting. Get medical attention immediately. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. ⚠ **WARNING:** Cancer and Reproductive Harm – www.P65Warnings.ca.gov. **For emergency, call your physician, local poison control center or local emergency room. For product health information, call: (800)481-4785. MÁX. VOC <450 g/L.For metal substrates only.**

CONTIENE: DESTILADOS DE PETRÓLEO. El vapor es perjudicial. Puede afectar el cerebro o el sistema nervioso y causar mareos, náuseas o dolores de cabeza. Produce irritación nasal, ocular, dérmica y de la garganta. **AVISO:** Algunos informes han asociado la sobreexposición ocupacional repetida y prolongada a solventes con daños permanentes en el cerebro y en el sistema nervioso. El uso incorrecto intencional, concentrando e inhalando deliberadamente el contenido del producto, puede ser perjudicial o mortal. Mantenga el producto lejos del calor y las llamas. Abra todas las ventanas y puertas para producir ventilación cruzada y evitar la acumulación de vapores. **Utilícelo solo con la ventilación adecuada.** No respire el polvo, los vapores ni el rocío. Asegure la entrada de aire fresco durante la aplicación y el secado. Si le lloran los ojos, tiene dolores de cabeza o mareos, o el control del aire demuestra que los niveles de vapor o rocío son superiores a los límites aplicables, use un respirador apropiado que se ajuste adecuadamente (aprobado por NIOSH, Instituto Nacional para la Seguridad y Salud Ocupacional) durante y después de la aplicación. Siga las instrucciones de uso del respirador proporcionadas por el fabricante. Evite el contacto con los ojos, la piel y la ropa. Lávese bien después de manipular el producto. **MANTENGA EL PRODUCTO FUERA DEL ALCANCE DE LOS NIÑOS. PRIMEROS AUXILIOS:** En caso de contacto con los ojos, enjuague inmediatamente con abundante agua durante por lo menos 15 minutos y busque atención médica de inmediato. En caso de contacto con la piel, lave bien con agua y jabón. Si tiene dificultades para respirar, abandone el área en busca de aire fresco. Si la dificultad experimentada persiste, busque atención médica de inmediato. En caso de ingestión, no induzca el vómito. Busque atención médica de inmediato. Elimine el absorbente contaminado, el recipiente y la cantidad no utilizada de acuerdo con las leyes locales, estatales y federales. ⚠ **ADVERTENCIA:** Cáncer y daños reproductivos – www.P65Warnings.ca.gov. **En caso de una emergencia, comuníquese con su médico, centro local para el control de venenos o clínica para emergencias. Para obtener más información sobre el producto y los posibles efectos en la salud, llame al (800) 481-4785. PROHIBIDA SU VENTA A MENORES DE EDAD; PRODUCTO ORIGINARIO DE E.U.A.**

SATISFACTION GUARANTEED: If you are dissatisfied with this product, contact Rust-Oleum Product Support at 800-481-4785 for product replacement or a full refund of the purchase price. Refer to product number and batch code.

SATISFACCIÓN GARANTIZADA: Si no está satisfecho con este producto, comuníquese con el Soporte Técnico de Rust-Oleum al 800-481-4785 para obtener un reembolso del total del precio de compra. Consulte el número de producto y el código de lote.

RUST-OLEUM CORPORATION
11 Hawthorn Pkwy., Vernon Hills, IL 60061
800-481-4785 rustoleum.com

Made in USA | Hecho en E.U.A.

©2018 Rust-Oleum Corporation 337678 0318

7777730 SATIN BLACK

0 20066 77777 7

SATIN WHITE 7791

• TRUSTED QUALITY SINCE 1921 •

RUST-OLEUM®

STOPS RUST®

PROTECTIVE ENAMEL

SUPERIOR DURABILITY
PREMIUM QUALITY

OIL-BASED

8 FL. OZ. (1/2 PINT) 236mL

DANGER!
COMBUSTIBLE LIQUID AND VAPOR.
HARMFUL OR FATAL IF SWALLOWED.
See other cautions on back panel.

¡PELIGRO!
LIQUIDO Y VAPORES COMBUSTIBLES.
DAÑINO O FATAL SI INGIBE.
Observar otras precauciones al dorso.

Rust-Oleum® Stops Rust® Oil-Based Enamels provide excellent rust prevention when applied directly to metal. They also offer excellent coverage, chip resistance and color retention. For even longer lasting protection, use a Stops Rust Primer first.

Painting Conditions: Use when temperature is above 50°F (10°C) and humidity is below 85% to ensure proper drying. Do not apply to surfaces that exceed 200°F (93°C) or galvanized metal. **Preparation:** Remove loose paint and rust with a wire brush or sandpaper. Lightly sand glossy surfaces. Clean surface with soap and water, rinse and let dry. **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. **Painting:** Stir thoroughly. If thinning is necessary, thin material only with mineral spirits or acetone. For brush or roller, thin no more than 5%. Apply with a good quality brush, roller or spray gun. **Recoat Times:** May recoat when fully dry, usually in 24 hours. Dries to the touch in 2-4 hours and to handle in 5-9 hours, at 70°F (21°C) – 50% relative humidity. Allow more time at cooler temperatures and higher humidity. **Clean-up:** Clean brush, roller and other tools with mineral spirits.

CONTAINS PETROLEUM DISTILLATES. Vapor Harmful. May affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, skin, nose and throat irritation. **NOTICE:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Keep away from heat and flame. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. **Use only with adequate ventilation.** Do not breathe dust, vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for use. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. **KEEP OUT OF REACH OF CHILDREN. FIRST AID:** In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention immediately; for skin, wash thoroughly with soap and water. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. If swallowed, do not induce vomiting. Get medical attention immediately. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. ⚠ **WARNING:** Cancer and Reproductive Harm – www.P65Warnings.ca.gov. **For emergency, call your physician, local poison control center or local emergency room. For product health information, call: (800)481-4785. MÁX. VOC <450 g/L.For metal substrates only.**

CONTIENE: DESTILADOS DE PETRÓLEO. El vapor es perjudicial. Puede afectar el cerebro o el sistema nervioso y causar mareos, náuseas o dolores de cabeza. Produce irritación nasal, ocular, dérmica y de la garganta. **AVISO:** Algunos informes han asociado la sobreexposición ocupacional repetida y prolongada a solventes con daños permanentes en el cerebro y en el sistema nervioso. El uso incorrecto intencional, concentrando e inhalando deliberadamente el contenido del producto, puede ser perjudicial o mortal. Mantenga el producto lejos del calor y las llamas. Abra todas las ventanas y puertas para producir ventilación cruzada y evitar la acumulación de vapores. **Utilíceło solo con la ventilación adecuada.** No respire el polvo, los vapores ni el rocío. Asegure la entrada de aire fresco durante la aplicación y el secado. Si le lloran los ojos, tiene dolores de cabeza o mareos, o el control del aire demuestra que los niveles de vapor o rocío son superiores a los límites aplicables, use un respirador apropiado que se ajuste adecuadamente (aprobado por NIOSH, Instituto Nacional para la Seguridad y Salud Ocupacional) durante y después de la aplicación. Siga las instrucciones de uso del respirador proporcionadas por el fabricante. Evite el contacto con los ojos, la piel y la ropa. Lávese bien después de manipular el producto. **MANTENGA EL PRODUCTO FUERA DEL ALCANCE DE LOS NIÑOS. PRIMEROS AUXILIOS:** En caso de contacto con los ojos, enjuague inmediatamente con abundante agua durante por lo menos 15 minutos y busque atención médica de inmediato. En caso de contacto con la piel, lave bien con agua y jabón. Si tiene dificultades para respirar, abandone el área en busca de aire fresco. Si la dificultad experimentada persiste, busque atención médica de inmediato. En caso de ingestión, no induzca el vómito. Busque atención médica de inmediato. Elimine el absorbente contaminado, el recipiente y la cantidad no utilizada de acuerdo con las leyes locales, estatales y federales. ⚠ **ADVERTENCIA:** Cáncer y daños reproductivos – www.P65Warnings.ca.gov. **En caso de una emergencia, comuníquese con su médico, centro local para el control de venenos o clínica para emergencias. Para obtener más información sobre el producto y los posibles efectos en la salud, llame al (800) 481-4785. PROHIBIDA SU VENTA A MENORES DE EDAD; PRODUCTO ORIGINARIO DE E.U.A.**

SATISFACTION GUARANTEED: If you are dissatisfied with this product, contact Rust-Oleum Product Support at 800-481-4785 for product replacement or a full refund of the purchase price. Refer to product number and batch code.

SATISFACCIÓN GARANTIZADA: Si no está satisfecho con este producto, comuníquese con el Soporte Técnico de Rust-Oleum al 800-481-4785 para obtener un reembolso del total del precio de compra. Consulte el número de producto y el código de lote.

RUST-OLEUM CORPORATION
11 Hawthorn Pkwy., Vernon Hills, IL 60061
800-481-4785 rustoleum.com
Made in USA | Hecho en E.U.A.

©2018 Rust-Oleum Corporation 337666 0318

7791730 SATIN WHITE

0 20066 77917 7