

PROJECT DETAILS QUICK GLANCE	
KIT COVERS - UP TO 200-250 SQ. FT.	# COATS NEEDED - 1 COAT
# GARAGE - 1 CAR	CLEAN-UP - SOAP & WATER
WALK-ON READY- 24 HOURS DRIVE-ON READY- 3 DAYS	APPLY WHEN WEATHER IS - BETWEEN 60° F - 85° F
BEST FOR - RESIDENTIAL GARAGES, BASEMENTS, WORKSHOPS, LAUNDRY ROOMS & MORE	

FEATURES & BENEFITS	
DRIVE ON IN 3 DAYS	1 COAT APPLICATION
NO HOT TIRE PICK-UP	PROVIDES AN EASY-TO-CLEAN SHOWROOM QUALITY APPEARANCE
ABRASION & CHEMICAL RESISTANT	WATERPROOFING SEALER

KIT INCLUDES

CONCRETE ETCH

DECORATIVE CHIPS

PART A

PART B

STIR STICK

INSTRUCTIONAL SHEET

GARAGE FLOOR COATING KIT

EASY 3-STEP APPLICATION

1 PREPARE SURFACE

Read full instructions before starting project
Clean and degrease entire floor
Scrub heavily-soiled areas
Etch entire floor with concrete etch (included)
Rinse thoroughly & allow to dry completely

2 MIX EPOXYSHIELD®

Mix 2-part EPOXYSHIELD® formula

3 APPLY COATING

Trim outer edges
Apply coating in 4' x 4' sections with roller (after induction time)
If desired, sprinkle decorative chips (included) on freshly coated section

RUST-OLEUM CORPORATION
11 Hawthorn Pkwy., Vernon Hills, IL 60061
888-683-5667 rustoleum.com/garage
Made in USA | Hecho en U.S.A.
©2020 Rust-Oleum Corporation 353384 0420

Limiting Warnings: Rust-Oleum Corporation guarantees product performance when the product is applied according to the label directions. If you are dissatisfied with this product, you may not receive a remedy or other refund if the original purchase price is replaced with the product's legal value. We do not guarantee the product against factors beyond our control, such as damage to the product by others, poor condition of the substrate, multiple surface preparation, structural defects, improper application, etc. We will not be responsible for labor or the cost of labor for removal or application of any product or replacement of any surface.

General Label: Rust-Oleum Corporation garantiza el rendimiento de productos cuando se aplican de acuerdo con las instrucciones que figuran en la etiqueta. Si no está satisfecho con este producto, la única solución posible es un reembolso del precio de compra original o el reembolso por el producto de legal valor. No garantizamos el rendimiento del producto en condiciones que están fuera de nuestro control, como el daño ocasionado al producto por terceros, o mal estado del sustrato, uso indebido o preparación de la superficie, defectos estructurales, uso indebido aplicación, etc. No nos hacemos responsables de la mano de obra ni del costo de la mano de obra para la remoción o aplicación de cualquier producto o del reemplazo de cualquier superficie.

TINT BASE 252625

0 20066 19395 9

* Per ASTM D-2486 when compared to Rust-Oleum 1-Part Concrete & Garage Floor Paint + Primer

SAFETY INFORMATION

CONTAINS: Epoxy Resin, Cyclohexylol Polyamine and Glycid Ethers. May cause allergic skin reaction. Harmful if swallowed. Causes eye, skin, nose and throat irritation. Use only with adequate ventilation. Do not breathe vapors. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness wear an appropriate, properly fitted respirator (NIOSH approved) or leave the area to obtain fresh air. Avoid contact with eyes, skin or clothing. Wash thoroughly after handling. First Aid: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. In case of eye contact, wash immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, do not induce vomiting. Get medical attention immediately. **KEEP OUT OF REACH OF CHILDREN.** ⚠️ **WARNING:** Cancer and Reproductive Harm - www.P65Warnings.gov.

INFORMACIÓN DE SEGURIDAD

CONTIENE: Resina Epoxica, Poliamina ciclohexilica, y Éteres de Glicol. Provoca irritación en los ojos, la piel, la nariz y la garganta. Podría provocar una reacción en la piel. Nocivo si se ingiere. Use únicamente con la ventilación adecuada. Asegure la entrada de aire fresco durante la aplicación y el secado. Si experimenta lagrimeo de ojos, dolor de cabeza o mareos, aumente la cantidad de aire fresco. Luego de cada uso, limpie el recipiente. Evite el contacto con los ojos, la piel y la ropa. Lávese bien después de manipular el producto. **PRIMEROS AUXILIOS:** En caso de contacto con los ojos, lávelos inmediatamente con agua en abundancia durante al menos 15 minutos y obtenga atención médica de inmediato; en caso de contacto con la piel, lávese bien con agua y jabón. Si tuviera dificultad para respirar, abandone el área y vaya a un sitio con aire fresco. Si se ingiere, no induzca el vómito. Obtenga atención médica de inmediato. **MANTENGA EL PRODUCTO FUERA DEL ALCANCE DE LOS NIÑOS. MANTENGA EL PRODUCTO FUERA DEL ALCANCE DE LOS NIÑOS.** ⚠️ **ADVERTENCIA:** Cáncer y daños reproductivos - www.P65Warnings.gov.

- OTHER SUPPLIES NEEDED
- ☐ Stiff bristle broom or scrub brush

☐ Roller frame, tray, 3/8" nap cover

☐ Extension pole

☐ Squeegee (for the most effective cleaning and to speed drying)

- OPTIONAL
- ☐ Rust-Oleum Cleaner & Degreaser

☐ Rust-Oleum Anti-Skid Additive

☐ Rust-Oleum Concrete Patch & Repair

☐ Additional Rust-Oleum Decorative Chips

Rust-Oleum® CROSS-LINKING TECHNOLOGY™

Unachievable with One-Part Paints

Rust-Oleum® CROSS-LINKING TECHNOLOGY™ FORMS A BOND THAT IS STRONGER THAN CONCRETE & HELPS PREVENT CONCRETE FROM CHIPPING, CRACKING & DUSTING.

NO PEEL PROMISE

RUST-OLEUM® EPOXYSHIELD®

#1 TRUSTED BRAND FOR PROTECTION

1 CAR GARAGE KIT

1 CAR GARAGE KIT

5X MORE DURABLE* THAN 1-PART EPOXY

DRIVE ON IN 3 DAYS

GARAGE FLOOR COATING KIT

WATER-BASED 2-PART EPOXY

No Hot Tire Pick-Up

Excellent Wear & Chemical Resistance

100% Satisfaction Guarantee

3.75 QTS (120 FL.OZ./3.54L)

KIT INCLUDES: 2-PART EPOXY FLOOR SYSTEM, CONCRETE ETCH, DECORATIVE CHIPS, STIR STICK AND INSTRUCTION SHEET (ENGLISH/ESPAÑOL)
FLOOR COLOR SHOWN IN GLACIER GRAY

THIS KIT CONTAINS TINT BASE

32 COLORS AVAILABLE AT THE PAINT COUNTER SEE TOP FOR DETAILS

KIT COVERS: UP TO 200-250 SQ. FT.

DANGER! CAUSES EYE AND SKIN BURNS. VAPOR HARMFUL. READ OTHER CAUTIONS ON THE BACK PANEL. PELIGRO! CAUSA QUE MAJURAS EN LA PIEL Y LOS OJOS. LEA ATENTAMENTE LAS ADVERTENCIAS ADICIONALES EN LA PARTE POSTERIOR.

NO PEEL PROMISE

RUST-OLEUM® EPOXYSHIELD®

#1 TRUSTED BRAND FOR PROTECTION

1 CAR GARAGE KIT

5X MORE DURABLE* THAN 1-PART EPOXY

DRIVE ON IN 3 DAYS

GARAGE FLOOR COATING KIT

WATER-BASED 2-PART EPOXY

No Hot Tire Pick-Up

Excellent Wear & Chemical Resistance

100% Satisfaction Guarantee

3.75 QTS (120 FL.OZ./3.54L)

KIT INCLUDES: 2-PART EPOXY FLOOR SYSTEM, CONCRETE ETCH, DECORATIVE CHIPS, STIR STICK AND INSTRUCTION SHEET (ENGLISH/ESPAÑOL)

THIS KIT CONTAINS TINT BASE

32 COLORS AVAILABLE AT THE PAINT COUNTER SEE TOP FOR DETAILS

KIT COVERS: UP TO 200-250 SQ. FT.

DANGER! CAUSES EYE AND SKIN BURNS. VAPOR HARMFUL. READ OTHER CAUTIONS ON THE BACK PANEL. PELIGRO! CAUSA QUE MAJURAS EN LA PIEL Y LOS OJOS. LEA ATENTAMENTE LAS ADVERTENCIAS ADICIONALES EN LA PARTE POSTERIOR.