

KRUD KUTTER® ULTRA POWER SPECIALTY ADHESIVE REMOVER

DESCRIPTION AND USES

Krud Kutter[®] Ultra Power Specialty Adhesive Remover is designed to quickly remove adhesive, asphalt, blacktop, carbon black, caulk, diesel soot, duct tape, foam, fresh oilbased paint and stain, liquid insulation, liquid nails, mastic, road & roofing tar, silicone sealant, water seal and more.

Ultra Power Specialty Adhesive Remover is effective on most surfaces. Not recommended on varnish, suede, leather, silk, rubber or elastic items.

IMPORTANT: Always test first on an inconspicuous area.

PRODUCTS

SKU	DESCRIPTION
302805	32 oz. Trigger Sprayer
302815	32 oz. Trigger Sprayer
302464	32 oz. Trigger Sprayer
UP05	5- Gallon Pail
UP55	55-Gallon Drum

PRODUCT APPLICATION

DIRECTIONS - WET SURFACE

Using a disposable cotton towel, remove as much wet solution as possible. Apply remover and allow to penetrate for 2-5 minutes. Peel, scrape or wipe. Rinse.

DIRECTIONS - DRY SURFACE

Remove as much dry solution as possible by scraping clean. Apply remover and let set up for 30-60 minutes. Peel, scrape or wipe. Rinse.

DANGER: Contains petroleum distillates. Eye and skin irritant. Use in well ventilated area. Do not use near heat, sparks or flames. **FIRST AID:** If swallowed, take large amounts of water. Do not induce vomiting. Get medical attention immediately. In case of contact with eyes or skin, flush with water for 15 minutes. If irritation persists, seek medical attention. Safety Data Sheets available. KEEP OUT OF REACH OF CHILDREN. General Purpose Adhesive Remover 20% VOC Compliant.

PHYSICAL PROPERTIES	
	ULTRA POWER SPECIALTY ADHESIVE REMOVER
Composition	D-Limonene Terpene, Dipropylene Glycol Mono Methyl Ether
рН	3.5
VOC	Consumer Weight Percent - 10%
Shelf Life	NA
Flash Point	172°F (78°C)
Warning!	DANGER: Contains petroleum distillates. Eye and skin irritant. Use in well ventilated area. Do not use near heat, sparks or flames. FIRST AID: If swallowed, take large amounts of water. Do not induce vomiting. Get medical attention immediately. In case of contact with eyes or skin, flush with water for 15 minutes. If irritation persists, seek medical attention. Safety Data Sheets available. KEEP OT OF REACH OF CHILDREN. General Purpose Adhesive Remover 20% VOC Compliant.
Safety Information	For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Rust-Oleum Corporation
11 Hawthorn Parkway Phone: 800-466-7126
Vernon Hills, Illinois 60061 www.rustoleum.com/

Phone: 800-466-7126 Form www.rustoleum.com/krudkutter Rev.:

Form: GDH-526 Rev.: 120921