



RUST-OLEUM® FROSTED GLASS

DESCRIPTION AND USES

Rust-Oleum® Frosted Glass is a finish that obscures vision but lets light shine through painted objects. Ideal on glass doors, windows, skylights, outside of shower doors and greenhouses. For a decorative effect, use a stencil to create an etched look on mirrors, shower doors, glass accessories and more. For use on interior surfaces only.

PRODUCTS

SKU	DESCRIPTION (Aerosol)
342600	Frosted Glass

PRODUCT APPLICATION

SURFACE PREPARATION

Remove all dirt, grease, oil, salt, and chemical contaminants by washing the surface with soap and water and let dry.

APPLICATION

Use outdoors or in a well-ventilated area such as an open garage. Use when temperature is between 50°F (10°C) and 90°F (32°C) and humidity is below 65% to ensure proper drying. Do not apply to surfaces that are exposed to repeated water contact such as the inside of a shower door. Avoid spraying in very windy and dusty conditions. Cover surrounding area to protect from spray mist.

Shake can vigorously for two minutes after the mixing ball begins to rattle. If mixing ball fails to rattle, DO NOT STRIKE CAN. Contact Rust-Oleum. Shake often during use. Hold can upright 10-12" from the surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can the same distance from the surface. Keep the can in motion while spraying. Apply 2 or more "wet" coats a few minutes apart for best appearance. (A "wet" coat should appear shiny as it is applied to the surface.) WAIT 10 MINUTES FOR FROST EFFECT. **Do not use near open flame.**

PRODUCT APPLICATION (cont.)

DRY & RECOAT

Dry and recoat times are based on 70°F (21°C) and 50% relative humidity. Allow more time at cooler temperatures. May recoat at anytime. Dries completely in 5-10 minutes.

CLEAN-UP

When finished spraying, clear spray valve by turning can upside down and pushing spray button for 5 seconds. Clean up wet paint with xylol or mineral spirits. Throw away empty can in trash pickup. Do not burn or place in home trash compactor.

Please note: Frosted surfaces may be cleaned with a household glass cleaner and soft cloth or hand-washed with liquid soap and water. Do not place items in dishwasher. To remove frosted finish from glass, use lacquer thinner or acetone.

CLOGGING

If the valve clogs, twist and pull off spray tip and rinse in a solvent such as mineral spirits. Do not insert any object into can valve opening.

	TECHNICAL DATA	SPC-97
• TRUSTED QUALITY SINCE 1921 • RUST-OLEUM® SPECIALTY	RUST-OLEUM® FROSTED GLASS	

PHYSICAL PROPERTIES

		FROSTED GLASS SPRAY
Resin Type		Acrylic Lacquer
Pigment Type		Proprietary
Solvents		Acetone, N-Butyl Acetate, Xylene
MIR		1.35 Max
Fill Weight		11 ounces
Practical Coverage (assumes 15% material loss)		Approximately 7 sq.ft./can (0.63 m ² /can)
Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity	Touch	5 minutes
	Fully Dry	10 minutes
	Recoat	Anytime
Dry Heat Resistance		200°F (93°C)
Shelf Life		5 years
Flash Point		-156°F (-104°C)
Safety Information		For additional information, see SDS

Calculated values are shown and may vary from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Rust-Oleum Corporation
11 Hawthorn Parkway
Vernon Hills, Illinois 60061

Phone: 800-481-4785
www.rustoleum.com

Form: ARJ-1783
Rev.: 100223