• TRUSTED QUALITY SINCE 1921 •

RUST-OLEUM®

glitter

INTERIOR WALL EFFECT

ROSE GOLD

buildable glitter effect with multiple coats of paint

NET 28 FL OZ. (828mL)

EXTRA SPACE IN CONTAINER ALLOWS ROOM FOR STIRRING.

GLITTER INTERIOR WALL EFFECT is an intense glitter paint that provides a multi-dimensional shimmer and sparkle. Can be applied to drywall, wood, metal, plastic and hardboard. Formulated to provide a decorative glitter finish to most interior surfaces.

READ ALL DIRECTIONS BEFORE BEGINNING PROJECT.

Painting Conditions: For use on interior surfaces only. Do not apply paint on surfaces exposed to high humidity. Use when temperature is between 50°F (10°C) and 90°F (32°C) and humidity is below 85% to ensure proper drying.

Preparation: Remove loose paint and rust with wire brush or sandpaper. Lightly sand glossy surfaces. Clean with soap and water, rinse and let dry. Tape around the area you wish to paint before beginning. **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS SUCH AS BRAIN DAMAGE. ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Priming: To provide superior adhesion, Zinsser® Bulls Eye 1-2-3® white primer is recommended on bare wood, drywall, metal and other porous surfaces. After priming bare wood, sand lightly to smooth surface. Follow primer manufacturer's instructions for dry time.

Basecoat: After priming and for best results, use a non-flat, pale pink paint as a basecoat. Follow basecoat manufacturer's instructions for dry time.

Painting: Rust-Oleum® Glitter Interior Wall Effect can be applied with a roller, brush or paint sprayer. Apply multiple thin, uniform coats. Stir paint every couple of minutes during application. The Glitter Paint may appear to have a gray tint inside the can and when applied. This will disappear as the paint dries on the surface. **ROLL:** Stir thoroughly. Use a 3/8" nap roller for best results. Fully wet roller with paint and remove excess before applying to wall. Roll glitter on the wall by rolling up and down as well as side to side until it is evenly distributed on the surface. **BRUSH:** Stir thoroughly. Use a good quality synthetic brush. Brush light coats and spread glitter evenly over surface. For best results, alternate brushing directions with successive coats. Use light, even strokes to ensure the smoothest finish. **EDGING:** For edging tips and techniques, visit rustoleum.com. **SPRAY:** Stir thoroughly. Mix well in spray gun before application. Do not shake. Use fan pattern for best results. Approx. 1-2 hours for recoat.

Dry and Recoat Times: Based on 77°F (25°C) – 50% relative humidity. Allow more time at cooler temperatures. Dries to touch in 2 hours and to handle in 6 hours. Allow additional coats to dry 2-4 hours between coats. Wait 24 hours before using painter's tape over glitter coating. Hang pictures in 3-5 days. Fully dry in 7 days.

Clean-Up: Clean brush and other application tools immediately with soap and water. Follow spray gun manufacturer's instructions for cleaning equipment.

CAUTION: Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. **First Aid:** If you experience difficulty in breathing, leave area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes; get medical attention. If swallowed, get medical attention immediately. ⚠**WARNING:** Cancer and Reproductive Harm – www.P65Warnings.ca.gov. **KEEP OUT OF REACH OF CHILDREN. PROTECT FROM FREEZING. For emergency, call your physician, local poison control center or local emergency room. For product health information, call: (800) 481-4785.**

Max VOC: ≤ 50g/L

SATISFACTION GUARANTEED: If you are dissatisfied with this product, contact Rust-Oleum Product Support at 800-481-4785 for product replacement or a full refund of the purchase price. Refer to product number and batch code.

STEP 1:
Apply primer

STEP 2:
Apply basecoat color similar to glitter color

STEP 3:
Apply first coat of glitter for a shimmer effect

STEP 4:
Apply multiple coats of glitter until desired effect is achieved

PRECAUCIÓN: Evite el contacto con ojos, piel y ropa. Lávese bien después de manipular el producto. **Primeros auxilios:** Si tiene dificultades para respirar, abandone el área en busca de aire fresco. Si la dificultad persiste, busque asistencia médica de inmediato. En caso de contacto con los ojos, enjuague inmediatamente con abundante agua durante al menos 15 minutos y busque atención médica. En caso de ingestión, busque atención médica de inmediato. ⚠ **ADVERTENCIA:** Cáncer y daños reproductivos – www.P65Warnings.ca.gov. **MANTENGA EL PRODUCTO ALEJADO DEL ALCANCE DE LOS NIÑOS. EVITE EL CONGELAMIENTO. En caso de emergencia, llame a su médico, al centro de control de intoxicación o a la sala de emergencias de su localidad. Para obtener información sanitaria del producto, llame al: (800) 481-4785.**

360221 ROSE GOLD

0 20066 46909 2

RUST-OLEUM CORPORATION

11 Hawthorn Pkwy., Vernon Hills, IL 60061

800-481-4785 rustoleum.com

Made in USA | Hecho en E.U.A.

©2020 Rust-Oleum Corporation 360269 0120

• TRUSTED QUALITY SINCE 1921 •

RUST-OLEUM®

COPPER

buildable glitter effect with multiple coats of paint

NET 28 FL OZ. (828mL)

EXTRA SPACE IN CONTAINER ALLOWS ROOM FOR STIRRING.

GLITTER INTERIOR WALL EFFECT is an intense glitter paint that provides a multi-dimensional shimmer and sparkle. Can be applied to drywall, wood, metal, plastic and hardboard. Formulated to provide a decorative glitter finish to most interior surfaces.

READ ALL DIRECTIONS BEFORE BEGINNING PROJECT.

Painting Conditions: For use on interior surfaces only. Do not apply paint on surfaces exposed to high humidity. Use when temperature is between 50°F (10°C) and 90°F (32°C) and humidity is below 85% to ensure proper drying.

Preparation: Remove loose paint and rust with wire brush or sandpaper. Lightly sand glossy surfaces. Clean with soap and water, rinse and let dry. Tape around the area you wish to paint before beginning. **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS SUCH AS BRAIN DAMAGE. ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Priming: To provide superior adhesion, Zinsser® Bulls Eye 1-2-3® white primer is recommended on bare wood, drywall, metal and other porous surfaces. After priming bare wood, sand lightly to smooth surface. Follow primer manufacturer's instructions for dry time.

Basecoat: After priming and for best results, use a non-flat, reddish-brown paint as a basecoat. Follow basecoat manufacturer's instructions for dry time.

Painting: Rust-Oleum® Glitter Interior Wall Effect can be applied with a roller, brush or paint sprayer. Apply multiple thin, uniform coats. Stir paint every couple of minutes during application. The Glitter Paint may appear to have a gray tint inside the can and when applied. This will disappear as the paint dries on the surface. **ROLL:** Stir thoroughly. Use a 3/8" nap roller for best results. Fully wet roller with paint and remove excess before applying to wall. Roll glitter on the wall by rolling up and down as well as side to side until it is evenly distributed on the surface. **BRUSH:** Stir thoroughly. Use a good quality synthetic brush. Brush light coats and spread glitter evenly over surface. For best results, alternate brushing directions with successive coats. Use light, even strokes to ensure the smoothest finish. **EDGING:** For edging tips and techniques, visit rustoleum.com. **SPRAY:** Stir thoroughly. Mix well in spray gun before application. Do not shake. Use fan pattern for best results. Approx. 1-2 hours for recoat.

Dry and Recoat Times: Based on 77°F (25°C) – 50% relative humidity. Allow more time at cooler temperatures. Dries to touch in 2 hours and to handle in 6 hours. Allow additional coats to dry 2-4 hours between coats. Wait 24 hours before using painter's tape over glitter coating. Hang pictures in 3-5 days. Fully dry in 7 days.

Clean-Up: Clean brush and other application tools immediately with soap and water. Follow spray gun manufacturer's instructions for cleaning equipment.

CAUTION: Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. **First Aid:** If you experience difficulty in breathing, leave area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes; get medical attention. If swallowed, get medical attention immediately. ⚠**WARNING:** Cancer and Reproductive Harm – www.P65Warnings.ca.gov. **KEEP OUT OF REACH OF CHILDREN. PROTECT FROM FREEZING. For emergency, call your physician, local poison control center or local emergency room. For product health information, call: (800) 481-4785.**

Max VOC: ≤ 50g/L

SATISFACTION GUARANTEED: If you are dissatisfied with this product, contact Rust-Oleum Product Support at 800-481-4785 for product replacement or a full refund of the purchase price. Refer to product number and batch code.

STEP 1:
Apply primer

STEP 2:
Apply basecoat color similar to glitter color

STEP 3:
Apply first coat of glitter for a shimmer effect

STEP 4:
Apply multiple coats of glitter until desired effect is achieved

PRECAUCIÓN: Evite el contacto con ojos, piel y ropa. Lávese bien después de manipular el producto. **Primeros auxilios:** Si tiene dificultades para respirar, abandone el área en busca de aire fresco. Si la dificultad persiste, busque asistencia médica de inmediato. En caso de contacto con los ojos, enjuague inmediatamente con abundante agua durante al menos 15 minutos y busque atención médica. En caso de ingestión, busque atención médica de inmediato. ⚠**ADVERTENCIA:** Cáncer y daños reproductivos – www.P65Warnings.ca.gov. **MANTENGA EL PRODUCTO ALEJADO DEL ALCANCE DE LOS NIÑOS. EVITE EL CONGELAMIENTO. En caso de emergencia, llame a su médico, al centro de control de intoxicación o a la sala de emergencias de su localidad. Para obtener información sanitaria del producto, llame al: (800) 481-4785.**

360222 COPPER

0 20066 46910 8

RUST-OLEUM
CORPORATION

11 Hawthorn Pkwy., Vernon Hills, IL 60061
800-481-4785 rustoleum.com

Made in USA | Hecho en E.U.A.

©2020 Rust-Oleum Corporation 360270 0120