

SEAL KRETE

HEAVY-DUTY

CONCRETE & MASONRY WATERPROOFER

PRODUCT
DATA SHEET

Description: Water-based, 25% solids, acrylic waterproofing sealer designed for low density/porous vertical concrete and masonry surfaces.

Typical Uses:

- ✓ Split Face Block
- ✓ Galvanized Metal
- ✓ EIFS
- ✓ Stucco
- ✓ Adobe
- ✓ Concrete Walls
- ✓ Decorative Block
- ✓ Fluted Block
- ✓ Vinyl/Aluminum Siding

Important: Read all directions thoroughly. Recommended: Wear gloves and safety glasses.

SURFACE PREP*

All surfaces must be clean and dry. Remove any loose or peeling paint and excessive chalk. Repair all cracks and surface breaks. Cover windows, doors, etc., prior to application. Use caution when applying on windy days. Remove any overspray immediately with water.

APPLICATION

Do not apply if rain is expected within 12 hours. Temperatures should not fall below 50°F within 24 hours of application. Ready to use – do not dilute. Apply SEAL-KRETE Heavy-Duty using a garden sprayer, airless sprayer, brush or roller. Spray applications should be backrolled to assure proper surface penetration. Apply a minimum of 2 flood coats, allowing a minimum of 2 hours dry time between coats. SEAL-KRETE Heavy-Duty goes on milky white, which aids in complete surface application, but dries clear.

NEW STUCCO: Paint up to 3 weeks faster. Apply 2 coats of SEAL-KRETE Heavy-Duty 10 days after stucco has been placed to effectively lower surface pH. Paint when dry.

COLORED STUCCO: SEAL-KRETE Heavy-Duty can be applied to colored stucco during the curing process to reduce bleeding and discoloration.

COVERAGE: 50–300 sq.ft. per gallon. Coverage will vary based on surface porosity. Coverage of second coat application is 50% greater per gallon (see side panel).

DRY TIME: SEAL-KRETE Heavy-Duty typically dries in 2–4 hours, depending on temperature and humidity.

TOPCOATING: SEAL-KRETE Heavy-Duty can be topcoated when dry with latex, oil based or elastomeric coatings.

TINTING: SEAL-KRETE Heavy-Duty can be tinted up to 4 oz. per gallon using universal colorants.

CLEAN-UP & STORAGE: Clean all application tools with soap and water immediately after use. Store product in a dry area above 50°F (10°C). KEEP FROM FREEZING.

LIMITATIONS: Use on above-grade vertical surfaces. Do not apply if rain is forecast within 12 hours or if temperatures fall below 50°F within 24 hours of application. Do not use on swimming pools, birdbaths, water features, cedar, redwood or in areas where hydrostatic pressure is likely to develop.

**Sanding or removing paint containing lead may be hazardous. For information contact the National Lead Information Center at 1-800-424-LEAD or www.epa.gov/lead.*

FIRST AID: In case of eye contact, flush with water for 15 minutes. If irritation persists, get medical attention. In case of skin contact, wash thoroughly with soap and water. If swallowed, drink 1-2 glasses of water and immediately contact medical services regarding any instructions to induce vomiting.

KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.



Product	No.	Unit	UPC Code	Carton Bar Code	Carton Size (W x D x H)	Cube / Wt. (cubic ft / lbs)	Carton Qty	Pallet Qty
Heavy-Duty	700005	5 gallon	0 15944 70005 3	–	–	1.30 / 45.42	1	36



HEAVY-DUTY

CONCRETE & MASONRY WATERPROOFER

- PRO-GRADE DURABILITY
- INTERIOR/EXTERIOR USE
- UNCOATED VERTICAL SURFACES

TECHNICAL INFORMATION FOR USE ON VERTICAL SURFACES:

- Concrete
- Stucco
- Plaster
- EIFS
- Drywall
- Galvanized Metal
- Adobe
- Vinyl Siding
- Aluminum Siding
- Masonite
- Wood Fencing

SEAL-KRETE HEAVY-DUTY IS:

- Paintable
- Tintable
- Long-lasting
- Environmentally Safe

LIQUID PROPERTIES

- Solids: 25%
- Proprietary Acrylic Resin
- Water Based
- Odor: Slight
- Appearance: Milky White, Dries Clear
- VOC < 100 g/l – EPA Method 24 – Waterproofing Sealer Category

COVERAGE GUIDELINES

Material Coverage
Approx. sq.ft./gal.

Split-Face Block	50
Fluted Block	50
Concrete Block	80
Stucco	150
Concrete Slab / Tilt-ups	175
Wood Fencing	175
Aluminum Siding	300
Galvanized Metal	300
Adobe	100
Chalky Surfaces	300

Actual coverage will vary depending on porosity of surface. For second coat application, increase coverage by 50%.

LIMITED 5-YEAR WARRANTY: A limited 5-year warranty is available on the quality and performance of this product on a per job basis. For full details on this warranty program, contact our technical service department. Otherwise, manufacturer/seller makes no warranty of any kind, except that this product is free from defect and is of merchantable quality. Buyer remedy for breach of warranty is limited to replacement of product or refund of purchase price. Convenience Products will not be responsible for labor or cost of labor for removal or application of any product.

TECHNICAL SUPPORT: For more information on surface prep or application guidelines, or to obtain a Material Safety Data Sheet, call 1-800-323-7357, M-F (8:00 am–5:00 pm EST) or visit our website at www.seal-krete.com.

STOPS WATER PENETRATION

HI-SOLIDS FORMULA FOR USE ON SPLIT-FACE, FLUTED & DECORATIVE BLOCK

BINDS CHALKY SURFACES & STRENGTHENS MORTAR JOINTS

STOPS WATER PENETRATION



SEALS ALL TYPES OF POROUS VERTICAL MASONRY SURFACES



11 Hawthorn Pkwy., Vernon Hills, IL 60061
Questions or comments? Call 1-800-323-7357
www.seal-krete.com
©2016 Rust-Oleum Corp

64046-121216-SK