



VARATHANE® TOUCH UP MARKER

DESCRIPTION AND USES

Varathane® Premium Touch-Up Markers are a fast and easy way to touch up minor scratches on stained wood. Touch-Up Markers are suitable to repair minor scratches and blemishes on furniture, cabinets, moldings and floors. Use Varathane Premium Touch-Up Markers for staining hard to reach areas or to provide color highlights to arts and crafts.

PRODUCTS

SKU	DESCRIPTION
215352	Color Group 1
215353	Color Group 2
215354	Color Group 3
215355	Color Group 4
215356	Color Group 5
215357	Color Group 6
215358	Color Group 7
215359	Color Group 8
215360	Color Group 9
215361	Color Group 10

PRODUCT APPLICATION

SURFACE PREPARATION

Previously Stained Wood Surfaces - Remove any existing coatings using sandpaper or stripper. Prepare bare wood for staining by sanding in the direction of the grain. Begin with #120 grit sandpaper and progress through #150, #180 and #220 grits. Remove all sanding dust with a vacuum or clean rag dampened with mineral spirits. Soft woods such as pine, fir and maple require a wood conditioner. Use Varathane Premium Wood Conditioner before staining.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

PRODUCT APPLICATION (cont.)

TESTING COLOR

Be sure to test your marker to verify the desired color. To test, apply stain in an inconspicuous area. When testing on soft woods, be sure to sand and condition the test area first.

APPLICATION

Shake well before using. Remove cap and slowly depress marker by pressing lightly on the tip. Press pen down and apply the stain to the wood. Quickly wipe off excess using a soft, lint-free cloth. Replace cap tightly after each use.

DRY TIME

Touch-Up Markers dry to the touch in 30 minutes and can be handled in 1 hour. Dry times may be affected by temperature, humidity and ventilation.

	TECHNICAL DATA	VAR-15
	VARATHANE® TOUCH UP MARKER	

PHYSICAL PROPERTIES

		TOUCH UP MARKER
Resin Type		Alcohol Based
Pigment Type		Organic and Inorganic
Solvents		Alcohol Blends
Solids	By Weight	12.6-32.7%
	By Volume	7.9-20.4%
Volatile Organic Compounds		550-640 g/l
Recommended Dry Film Thickness (DFT) Per Coat		NA
Wet Film to Achieve DFT (unthinned material)		NA
Practical Coverage at Recommended DFT (assumes 15% material loss)		Varies with color
Dry Times at 70-80F (21-27°C) and 50% Relative Humidity	Touch	1 hour
	Handle	1 hour
Shelf Life		3 years
Flash Point		>93°F (34°C)
Safety Information		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.