

**RUST-OLEUM® Cold Galvanized Compound provides maximum rust protection when applied to clean, unpainted sheet metal, fences or any galvanized surface. Dried film contains 93% pure zinc. No topcoat required.**

**Directions:** Use outdoors, or in well-ventilated area, when temperature is above 50°F (10°C) and humidity is below 85% to ensure proper drying. Do not apply to surfaces that exceed 200°F (93°C). Avoid spraying in very windy, dusty conditions. Cover nearby objects to protect from spray mist.

Remove loose paint and rust with a wire brush or sandpaper. Lightly sand glossy surfaces. Clean with soap and water, rinse and let dry.

Shake can vigorously for one minute after mixing balls begin to rattle. Shake often during use. Hold can upright 12-16" from surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can the same distance from the surface and in motion while spraying. Apply 2 or more light coats a few minutes apart.

May recoat after 1 hour. Dries to the touch in 30 minutes, to handle in 1-2 hours and is fully dry in 24 hours at 70°F (21°C) – 50% relative humidity. Allow more time at cooler temperatures.

When finished spraying, clear spray valve by turning can upside down and pushing spray button for 5 seconds. If valve clogs, twist and pull off spray tip and rinse it in a solvent such as mineral spirits. Do not stick a pin or other object into the stem. Throw away empty can in trash pickup. Do not burn or place in home trash compactor.

**CONTAINS TOLUENE AND XYLENE. VAPOR HARMFUL. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. CAUSES EYE, SKIN, NOSE AND THROAT IRRITATION. HARMFUL IF SWALLOWED.**

**NOTICE:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Do not breathe vapors, spray mist, sanding dust or overspray. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA approved) or leave the area. Follow respirator manufacturer's instructions for respirator use. Avoid contact with eyes, skin and clothing. **Vapors may ignite explosively.** Keep away from heat, sparks and flame. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Do not smoke. **Use only with adequate ventilation.** Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Do not expose to heat or store at temperatures above 120°F. Exposure to heat or prolonged exposure to sun may cause bursting. Do not puncture or incinerate (burn) container. Replace cap after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, do not induce vomiting. Get medical attention immediately. **WARNING:** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm. **KEEP OUT OF REACH OF CHILDREN. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL. DO NOT STORE ABOVE 120°F (48°C).** **Unleaded—Safe for use on children's toys, furniture, etc.**

We stand behind our products. If you are dissatisfied with this product, contact our Customer Service Department for a refund of the product purchase price.

**CONTIENE TOLUENO Y XILENO. EL VAPOR ES DAÑINO. PUEDE AFECTAR AL CEREBRO O AL SISTEMA NERVIOSO CAUSANDO MAREOS, DOLORS DE CABEZA O NAUSEA. IRRITA LOS OJOS, LA PIEL, LA NARIZ Y LA GARGANTA. DAÑINO SI ES INGERIDO O TRAGADO. AVISO:** En algunos estudios se ha observado que la sobreexposición ocupacional repetida prolongada a los solventes causa daño permanente al cerebro y al sistema nervioso. No respire los vapores, la nube del rocío, el polvo del lijado, ni el sobre rocío. Para evitar la respiración del vapor o la niebla del rociado, abra las ventanas y puertas o use cualquier otro medio para asegurar la circulación de aire fresco durante la aplicación y el secado. Si experimenta lacrimación en los ojos, dolores de cabeza o mareos, aumente la circulación de aire fresco o use protección respiratoria (con certificación NIOSH/MSHA) o abandone el área. Por favor siga las instrucciones de los fabricantes para el uso apropiado del respirador. Evite contacto con los ojos, la piel y la ropa. **Los vapores pueden inflamarse explosivamente.** Mantenga alejado de fuentes caloríficas, chispas y llamas. Durante la aplicación del producto, apague las llamas y llamas pilotos, apague las estufas, calentadores, motores eléctricos y todas las otras fuentes de ignición hasta que todos los vapores hayan desaparecido. No fume. **Aplique el producto solamente con ventilación adecuada.** Evite la acumulación de los vapores abriendo todas las ventanas y puertas para lograr ventilación cruzada. No exponga el recipiente al calor ni lo almacene a temperaturas superiores a 120°F (48°C). La exposición al calor, o la exposición prolongada al sol puede causar una explosión. No perforo ni incinere (queme) el recipiente. Vuelva a colocar la tapa después de cada aplicación. **PRIMEROS AUXILIOS:** Si sufre dificultad para respirar, abandone el área y respire aire fresco. Si la dificultad para respirar persiste, busque asistencia médica inmediatamente. En caso de contacto con los ojos, enjuáguelos inmediatamente con suficiente agua durante un mínimo de 15 minutos y busque atención médica; en caso de contacto con la piel, lave completamente el área afectada con agua y jabón. En caso de ingestión del producto, no se induzca vómito. Llame un médico inmediatamente. **ADVERTENCIA:** Este producto contiene químicos que son conocidos en el Estado de California porque causan cáncer y defectos de nacimiento u otros daños al sistema reproductivo. **MANTENGA FUERA DEL ALCANCE DE LOS NIÑOS. EL USO INAPROPIADO INTENCIONAL CONCENTRANDO E INHALANDO EL CONTENIDO PUEDE SER DAÑINO O MORTAL. NO SE DEBE ALMACENAR A TEMPERATURAS SUPERIORES A 120°F (48°C). No contiene plomo—Puede utilizarse para los juguetes de los niños, muebles, etc.**



Contains no CFC's

An **rpm** Company



**RUST-OLEUM**  
**CORPORATION**

11 Hawthorn Pkwy, Vernon Hills, IL 60061  
[www.rustoleum.com](http://www.rustoleum.com)