

VISIT RUSTOLEUM.COM/GARAGE FOR INSTRUCTIONAL VIDEOS, FAQs AND TIPS & TECHNIQUES

RUST-OLEUM
ROCKSOLID
THE WORLD'S TOUGHEST COATINGS™

KIT FOR: Garage Floors, Driveways, Concrete, Sealers
APPROXIMATE: 1000 sq. ft. (930 sq. m.)
COVERAGE: 1000 sq. ft. (930 sq. m.)

PROJECT DETAILS QUICK GLANCE

DRIVE ON IN 1 DAY
NO HOT TIRE PICK-UP
EXCELLENT CHEMICAL RESISTANCE

**IT'S THAT
TOUGH!**

FEATURES & BENEFITS

DRIVE ON IN 1 DAY	20X STRONGER THAN EPOXY	1 COAT APPLICATION
NO HOT TIRE PICK-UP	EXTREME HIGH GLOSS	WATERPROOFING SEALER
EXCELLENT CHEMICAL RESISTANCE	SELF-LEVELING AND BUBBLE-FREE	LOW ODOR AND LOW VOC*
	EASY MIX BURST POUCH	

TRUSTED QUALITY SINCE 1921
RUST-OLEUM
ROCKSOLID
THE WORLD'S TOUGHEST COATINGS™

PEARLESCENT FLOOR COATING KIT



KIT INCLUDES:



OTHER SUPPLIES NEEDED:

- ROLLER FRAME
- EXTENSION POLE
- STIFF BRISTLE BROOM OR SCRUB BRUSH
- 3" PAINT BRUSH
- 5 QT. MIXING BUCKET
- OPTIONAL:
 - ANTI-FOAM ADDITIVE
 - HEAVY DUTY DEGREASER
 - CONCRETE PATCH AND REPAIR
 - PADDLE MIXER, DRILL
 - ROCKSOLID HIGH GLOSS CLEAR TOPCOAT
 - ROCKSOLID TEXTURED CLEAR TOPCOAT

**NO PEEL
PROMISE**

TRUSTED QUALITY SINCE 1921
RUST-OLEUM
ROCKSOLID
THE WORLD'S TOUGHEST COATINGS™

**1 CAR
GARAGE KIT**

EASY MIX BURST POUCH



PEARLESCENT FLOOR COATING KIT

PEARLESCENT FLOOR COATING KIT

**20X
STRONGER
THAN EPOXY**
**DRIVE ON
IN 1 DAY**

PEARLESCENT FLOOR COATING KIT

INDUSTRIAL-GRADE
POLYCURAMINE™

No Hot Tire Pickup
Superior Impact & Chemical Resistance
Showroom Quality Finish

**EXTREME
HIGH GLOSS**

2.5 QTs (80 FL OZ/2.36L)

KIT INCLUDES POLYCURAMINE POLYURETHANE TOPCOAT
MICA ADDITIVE, INSTRUCTIONS, BURST POUCH

PEARL BLACK

KIT COVERS: UP TO 200-250 SQ. FT.
DANGER: FLAMMABLE AND CAUSTIC FOR SKIN AND EYES.
PEEL OFF TOP COAT IMMEDIATELY AFTER FINISHING.
DO NOT RE-ENTRY UNTIL THE TOP COAT IS COMPLETELY DRY.

PEARLESCENT FLOOR COATING KIT

EASY APPLICATION

- PREPARE SURFACE**
Scrub heavily soiled areas. Remove dirt, grease, oil, and debris. Wash with detergent and water. Rinse thoroughly. Allow to dry completely. Thoroughly clean all concrete surfaces prior to application for maximum performance.
- BURST, SHAKE, POUR**
Roll out Add Polycuramine (shown front side). Spread and mix thoroughly. Spread and mix thoroughly. Spread and mix thoroughly. Spread and mix thoroughly.
- MIX IN MICA ADDITIVE**
Add Mica Additive to bucket. Mix with clean scoop. Included or provide mixer and drill for 5 minutes. Scuff all over concrete and mix thoroughly. Mix thoroughly.
- APPLY COATING**
Trim outer edges. Apply coating in 4 ft. x 4 ft. sections with roller.

VISIT RUSTOLEUM.COM/GARAGE FOR INSTRUCTIONAL VIDEOS, FAQS AND TIPS & TECHNIQUES

RUST-OLEUM

11 Hawthorne Parkway, Irvine, CA 92618
888-653-5667 rustoleum.com/garage
©2013 Rust-Oleum Corporation 30307-0001

SAFETY INFORMATION
See accompanying Material Safety Data Sheet (MSDS) for full product details.
CONTENTS: 2.5 QT (80 FL OZ) POLYCURAMINE, 1 QT (32 FL OZ) MICA ADDITIVE.
USE: For use on concrete floors, driveways, and other concrete surfaces.
WARNING: FLAMMABLE AND CAUSTIC. Avoid contact with skin and eyes. Wash thoroughly with soap and water if contact occurs.
PRECAUTIONS: Wear protective gloves and eye protection. Do not eat, drink, or smoke while using this product.
STORAGE: Store in original container in a cool, dry place. Do not store in areas where children or pets can access.
DISPOSAL: Dispose of unused product in accordance with local regulations.
REGULATORY INFORMATION: This product complies with all applicable federal, state, and local regulations.
OTHER INFORMATION: For more information, visit rustoleum.com/garage.



INFORMACIÓN DE SEGURIDAD


Ver hoja de datos de seguridad (SDS) para obtener toda la información.
CONTENIDO: 2.5 QT (80 FL OZ) POLYCURAMINE, 1 QT (32 FL OZ) MICA ADDITIVE.
USO: Para uso en pisos de concreto, caminos de concreto y otras superficies de concreto.
ADVERTENCIA: INFLAMABLE Y CAUSTICO. Evite el contacto con la piel y los ojos. Lave a fondo con agua y jabón si ocurre contacto.
PRECAUCIONES: Use guantes protectores y protección para los ojos. No coma, beba o fume mientras usa este producto.
ALMACENAMIENTO: Almacene en el envase original en un lugar fresco y seco. No almacene en áreas donde los niños o mascotas puedan acceder.
DESCARTADO: Descarte el producto sobrante de acuerdo con las regulaciones locales.
OTRA INFORMACIÓN: Para más información, visite rustoleum.com/garage.

REGULATORY INFORMATION
This product complies with all applicable federal, state, and local regulations.
OTHER INFORMATION
For more information, visit rustoleum.com/garage.

The revolutionary RockSolid® Polycuramine™ combines key attributes from multiple chemistries into one. This creates a durable, self-leveling, fast curing, extreme high gloss coating system, that can be completed in one day.

**20X STRONGER
THAN EPOXY**

POLYCURAMINE™ TECHNOLOGY



PENETRATES AND ATTACHES TO CONCRETE TO FORM A BONDING MATRIX.
SELF-LEVELING.
CURES WITH THE CONCRETE TO PREVENT CRACKING OR PEELING.