



**SUREGRIP®  
ALL PURPOSE ADHESIVE & WALL SIZE**

**DESCRIPTION AND USES**

Rust-Oleum® SureGrip® All Purpose Adhesive & Wall Size is a high performance powder adhesive for hanging all types of pre-pasted and non-pasted wallcoverings and borders. This adhesive is suitable for use with special and delicate wallpapers, non-woven coverings and fabrics. It readily dissolves in cold water without forming lumps, spreads easily, dries clear and is odorless. This all purpose adhesive is strippable and makes positioning easier. This product is an excellent wall size for preparing walls prior to the application of wallcoverings. It enhances bonding and allows for easy stripping later.

SureGrip All Purpose Adhesive & Wall Size is not intended for hanging borders or wallcoverings over existing vinyl wallcovering without the use of a primer. See "Existing Vinyl Wallcovering" under Application in next column for recommendations. SureGrip All Purpose Adhesive & Wall Size is not recommended for hanging heavy type II or II commercial wallcoverings.

**PERFORMANCE CHARACTERISTICS**

- Non-staining powder adhesive
- Ideal for murals, grass cloth, string and fabric
- Excellent for preparing wall surface prior to hanging, making positioning easier
- Easy to mix, dries clear

**PRODUCT**

SKU	DESCRIPTION
62008	8 Ounces

**PRODUCT APPLICATION**

**SURFACE PREPARATION**

Surfaces must be clean, dry, sound and free of dust, grease, wax, oil, old wallcovering adhesive, mold and mildew and other residue. Inspect the surface for paint bonding, loose wallcoverings, damaged wallboard or plaster. Remove old or loose wallcovering and residual wallcovering adhesive with DIF® Wallpaper Stripper. Repair unsound surfaces. Seal loose paint or damaged drywall and cured skim coats with Gardz® High Performance Sealer as needed.

**Mold & Mildew**

Eliminate pre-existing mold and mildew by washing the affected area with a solution of ¼ cup of bleach to 1 gallon of water. Wear protection to prevent skin and eye contact. Quickly wash off any solution that comes in contact with your skin. Do not add ammonia or other cleaning agents to the bleach solution. Rinse surface with clean water. Allow surface to dry thoroughly before applying wallcovering.

**PRODUCT APPLICATION (cont.)**

**SURFACE PREPARATION (cont.)**

**Drywall**

Wipe down with a damp cloth to remove residual joint compound dust prior to priming.

**Plaster**

New plaster must age at least 90 days before hanging wallcovering. Prime prior to installation.

**Glossy Surfaces**

Glossy paint, paneling, metal, glass, plastic, etc. should be primed with ShieldZ Universal or ShieldZ Clear Acrylic Wall Size prior to wallcovering installation. Metal surfaces should be primed with rust inhibiting Bulls- Eye® 1-2-3 Primer.

**Existing Vinyl Wallcovering**

This product is not intended for hanging wallcoverings over existing vinyl wallcoverings without the use of a primer. For hanging lightweight wallpaper or borders directly over unprimed vinyl, use SureGrip Universal Adhesive or SureGrip Border Adhesive for Wallpapered Surfaces.

**Textile/Delicate/Polyolefin/Polyester Backed Wallcoverings**

Take special care to keep the adhesive off the face of textile or delicate wallcovering. Some wallcovering can be stained by water alone. Test for stain resistance prior to installation and hang according to manufacturer's instructions.

**MIXING**

In a clean container, slowly mix the contents of carton with water as recommended on the carton. Stir until product is completely dissolved. Wait ten minutes before using, stirring occasionally. **Mix only the amount intended for use. Do not store unused mixed material.**

**APPLICATION**

Use only when temperature is between 50-100°F (10-38°C) and the relative humidity is less than 85%. Apply adhesive to the back of wallcovering with a brush, roller or pasting machine. Smooth the adhesive evenly over the entire wallcovering. Make sure sufficient adhesive is on edges. Make sure sufficient adhesive is on edges. Avoid contact with the surface of embossed or delicate wallcovering. Book and hang wallcovering according to the manufacturer's instructions.



## **SUREGRIP® ALL PURPOSE ADHESIVE & WALL SIZE**

### **PRODUCT APPLICATION (cont.)**

#### **COVERAGE**

Spread rate may differ with various wallcoverings.

#### **DRY TIME**

Drying time will vary depending on the wallcovering type, temperature, ventilation and humidity in the room.

#### **CLEAN-UP**

Remove excess adhesive on or around the wallcovering immediately with clean water. Additional effort may be required if adhesive is allowed to contact the surface of embossed or textured vinyl. Close container tightly after each use.

#### **TOOL CLEAN-UP**

Clean tools with warm water.

#### **STORAGE**

Protect from freezing. Always keep the container tightly closed and store in a cool dry place at temperatures between 40-100°F (4-38°C)



**SUREGRIP®  
ALL PURPOSE ADHESIVE & WALL SIZE**

**PHYSICAL PROPERTIES**

	<b>ALL PURPOSE ADHESIVE &amp; WALL SIZE</b>
<b>Resin Type</b>	Starch-based Adhesive
<b>Solvents</b>	Water
<b>Appearance</b>	Clear
<b>Odor</b>	Mild
<b>Solids by Weight</b>	100%
<b>Volatile Organic Compounds (when mixed with water)</b>	<10 g/l (0.083 lbs./gal.)
<b>Practical Coverage at Recommended DFT (assumes 15% material loss)</b>	Coverage depends on the surface conditions and thickness of application.
<b>Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity</b>	Drying time will vary depending on the wallcovering type, temperature, ventilation and humidity in the room.
<b>Shelf Life</b>	2 years
<b>Flammability</b>	Non-flammable
<b>Safety Information</b>	For additional information, see SDS

Calculated values are shown and may vary from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.