



**ALLPRIME™ INTERIOR AND EXTERIOR
PREMIUM OIL BASE SEALER AND STAIN BLOCKER**

DESCRIPTION AND USES

Zinsser® AllPrime™ Interior and Exterior Oil Base Sealer and Stain Blocker is a high solids, low VOC, oil-based primer designed for interior or exterior surfaces where an oil-base primer is desired. Oil Base Sealer and Stain Blocker provides excellent penetration and flexibility and has excellent adhesion and stain blocking properties. Oil Base Sealer and Stain Blocker has excellent adhesion to dense, glossy surfaces such as enamel paints and varnishes, paneling, laminates, and ceramic tile without the need for sanding or de-glossing.

Oil Base Sealer and Stain Blocker is recommended for application on interior and exterior surfaces that have been damaged by fire, smoke or water. Interior surfaces include new or previously painted drywall, cured plaster and cement-based coatings, wood (including pine fir, cedar, redwood, and plywood), metal (including aluminum, iron, steel, and copper), vinyl, PVC, masonry (including stucco, concrete block, poured concrete, and brick). Exterior surfaces include new or previously painted wood (including pine, fir, cedar, redwood, and pressure-treated wood), hardboard, metal (including aluminum, iron, steel, and copper), vinyl and PVC.

MPI #5, #45, #46, #69, #79, #136 Certified. Refer to the MPI website for the most current listing of MPI certified products.

PERFORMANCE CHARACTERISTICS

- Fast drying – Recoat in less than 2 hours
- Sticks to all surfaces and sands easily
- Designed for interior and exterior surfaces
- High hiding formula blocks most stains
- Excellent for sealing water-soluble tannin bleed on cedar and redwood
- Easy paint thinner clean-up

PRODUCTS

SKU	DESCRIPTION
3654	1 Quart
3651	1 Gallon
3650	5 Gallons

PRODUCT APPLICATION

COLOR/TINTING

Oil Base Sealer and Stain Blocker is white but may be tinted to off-white and pastel shades by adding no more than 2 oz. (59 ml) universal colorant per gallon. Tinting the primer towards the topcoat improves the hiding power of the topcoat.

PRODUCT APPLICATION (cont.)

SEALING

Oil Base Sealer and Stain Blocker seals porous surfaces with a smooth, easily sanded film so paints have better coverage and consistent sheen. Oil Base Sealer and Stain Blocker helps bind chalky surfaces and is excellent for sealing chalky plaster and paints.

STAIN BLOCKING

Oil Base Sealer and Stain Blocker effectively blocks stains from water, nicotine, smoke, graffiti, crayon and rust. Oil Base Sealer and Stain Blocker seals all types of wood, is an excellent tannin blocker and is recommended for priming bare cedar and redwood. Some stains may require a second coat.

SURFACE PREPARATION

Surfaces should be clean, dry, sound and free of dust, dirt, excessive chalky material, grime, grease, oil, wax, mildew, wallpaper, adhesive or any contamination that may interfere with adhesion. If unsure of cleanliness, always wash surface with an appropriate ammoniated cleaning solution or solvent (do not use TSP as a cleaner). Remove any peeling and/or unsound coatings. Sand any remaining paint film edges smooth. Lightly sand exposed exterior wood with 80 to 100 grit sandpaper to remove loose or weathered wood fibers and mill glaze. When priming over stained areas, first attempt to remove as much of the stain as possible by washing, sanding, scraping, etc. Remove exterior mold & mildew with Zinsser Jomax® Mildew Killer and House Cleaner. Remove interior mildew with an interior mildew cleaner. Allow surface to dry completely before priming. Countersink exposed nail heads, spot prime and fill all nail holes and gouges with Zinsser Ready Patch® spackling compound. Wire brush rusty areas. Spot prime knots and sap streaks with B-I-N® Primer-Sealer before whole surface priming with Cover Stain Oil-Based Primer.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-Approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.



**ALLPRIME™ INTERIOR AND EXTERIOR
PREMIUM OIL BASE SEALER AND STAIN BLOCKER**

PRODUCT APPLICATION (cont.)

LIMITATIONS

Oil Base Sealer and Stain Blocker is not intended for application to floors, decks, roof surfaces or any surface subject to immersion or prolonged contact with water. Do not mix or intermix Oil Base Sealer and Stain Blocker with other oil-base or water-base products.

MIXING

Mix thoroughly to ensure any settled pigment is re-dispersed. Oil Base Sealer and Stain Blocker is designed to be used without thinning.

APPLICATION

Apply only when air, material, and surface temperatures are between 40-90°F (4-32°C) and the relative humidity is less than 85%. Shake or mix thoroughly before using. In most cases only one coat is necessary to prime most surfaces. If excessive absorption occurs over very porous substrates a second coat may be necessary. Spot priming is recommended only under high-hiding topcoat paints. For best results, prime entire surface before painting. Apply with a high quality natural or synthetic brush, roller, pad or sprayer. Follow manufacturer's instructions when using spray equipment. For airless spraying, use a 0.015 to 0.017" tip at 1800 to 2200 psi.

PRODUCT APPLICATION (cont.)

DRY TIME

In most cases Oil Base Sealer and Stain Blocker will dry to the touch in 35 minutes and can be recoated after 2 hours. The dry primer film develops full adhesion in 4-7 days. Lower temperatures, higher humidity and the addition of tint will prolong the dry and cure time.

CLEAN-UP

Clean up spills and paint drips with a rag soaked in mineral spirits or paint thinner. If spills or drips have dried, use paint remover. Application tools may be cleaned using paint thinner. Follow manufacturer's directions to clean spray equipment. Dispose of unused or unwanted product in accordance with local laws regulating solvent-based coatings.



**ALLPRIME™ INTERIOR AND EXTERIOR
PREMIUM OIL BASE SEALER AND STAIN BLOCKER**

PHYSICAL PROPERTIES

		OIL BASE SEALER AND STAIN BLOCKER
Resin Type		VT Modified Alkyd
Pigment Type		Calcium Carbonate, Talc, Titanium Dioxide
Solvents		Aromatic Hydrocarbons
Weight	Per Gallon	12.3 lbs.
	Per Liter	1.47 kg
Solids	By Weight	77.1%
	By Volume	57.1%
Volatile Organic Compounds		350 g/l (2.91 lbs./gal.)
Recommended Dry Film Thickness (DFT) per Coat		2.0-2.5 mils (50-62.5µ)
Wet Film to Achieve DFT (Unthinned material)		3.5-4.0 mils (87.5-100µ)
Practical Coverage at Recommended DFT (assume 15% material loss)		300-400 sq. ft./gal. (7.4-9.8 m ² /l) May vary with application method and surface porosity
Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity	Touch	35 minutes
	Recoat	2 hours
	Full Cure	4-7 days
Shelf Life		5 years
Flash Point		104°F (40°C)
Safety Information		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.