



ZINSSER® COVER STAIN® OIL-BASED PRIMER SPRAY

DESCRIPTION AND USES

Zinsser® Cover Stain® Oil-Based Primer is an all-purpose oil-based primer designed to provide excellent hiding power indoors and out. Cover Stain has excellent adhesion to dense surfaces such as enamel paints and varnishes, paneling, laminates and ceramic tile.

Cover Stain blocks stains from nicotine, graffiti, fire, smoke, water and dark colors. It seals interior /exterior bare wood, flat paint and spackling. It sticks to non-galvanized metal, glossy paint, ceramic, tile, glass and more.

Hard-To- Paint-Objects: Use on outdoor furniture, posts, and railings, shutters, wicker, picture frames, chairs, arts & crafts.

PRODUCTS

| SKU | DESCRIPTION (Aerosol) |
|------|-----------------------|
| 3608 | 13 Ounces |
| 3609 | 16 Ounces |

PRODUCT APPLICATION

READ ALL INSTRUCTIONS CAREFULLY BEFORE STARTING PROJECT

SURFACE PREPARATION

Surfaces should be clean, dry, sound and free of dust, dirt, grime, grease, oil, wax, wallpaper adhesive or any contamination that may interfere with adhesion. Remove loose paint, dirt and rust. Mask off nearby objects.

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead paint dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE; ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

PRODUCT APPLICATION (cont.)

APPLICATION

Apply at room temperature of 70°F in a well ventilated area. Avoid high humidity. Shake can vigorously until the agitator ball inside the can rattles. If the ball does not rattle, **DO NOT STRIKE CAN.** Contact Rust-Oleum. Turn the can upside down and continue shaking for one minute. Shake occasionally during use. Spray 10-12" from object with short 'dusting' strokes.

DRY TIME

At normal temperatures, Cover Stain dry to the touch in 15 minutes and surfaces can be painted in 1 hour.

CLEAN-UP

Wipe off tip before storing. Clean up wet paint with mineral spirits. Throw away empty can in garbage pickup. Do not burn or puncture the can, even when empty.

CLOGGING

If valve clogs, twist and pull off spray tip and rinse it in a solvent such as mineral spirits. Do not stick a pin or other objects into the stem.



**ZINSSER® COVER STAIN®
OIL-BASED PRIMER SPRAY**

PHYSICAL PROPERTIES

| | | COVERSTAIN OIL-BASED PRIMER |
|---|---------------|---|
| Resin Type | | Modified Alkyd |
| Pigment Type | | Titanium Dioxide, Calcium Carbonate, Talc, Aluminum Silicate |
| Solvents | | Acetone, N-Butane, Petroleum Naphtha |
| MIR | | 0.70 Max |
| Fill Weight | | 13 ounces |
| Recommended Dry Film Thickness (DFT) per Coat | | 1.5-2.5 mils (37.5-62.5µ) |
| Practical Coverage at Recommended DFT (assume 15% material loss) | | 10-12 sq. ft./can (0.9-1.1 m ² /can) depending on application method and surface porosity |
| Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity | Touch | 15 minutes |
| | Recoat | After 1 hour |
| Shelf Life | | 5 years |
| Flash Point | | -141°F (-96°C) |
| Safety Information | | For additional information, see SDS |

Calculated values are shown and may vary from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.